


MICHAEL AAF (DUGWAY PROVING GROUND) (DPG)(KDPG) A 9 W UTC-7(-6DT) N40°11.84' SALT LAKE CITY
 W112°56.10' H-3D, L-9C, 11C
 4350 B TPA—See Remarks NOTAM FILE CDC Not insp. DIAP, AD
RWY 12-30: H10999X150 (ASPH-GRVD) PCN 73 R/B/W/T HIRL
RWY 12: PAPI(P4R)—GA 3.0° TCH 88'. Thld dsplcd 1000'.
RWY 30: PAPI(P4R)—GA 3.0° TCH 85'. Thld dsplcd 1000'.
ARRESTING GEAR/SYSTEM
RWY 12 HOOK E5 (965 FT)
SERVICE: LGT ACTIVATE PAPI RWY 12 and RWY 30; HIRL RWY 12-30; TWY LGTS—CTAF. Rwy 12-30 NW first 5000'
 HIRL OTS indef. **MILITARY—** JASU 1(A/M32A-86) 1(A/M32A-60) **FUEL** A++ . Aircard rqr. **OIL** O-156 **TRAN ALERT** Opr
 1400-0030Z‡ Mon-Thu exc hol.
MILITARY REMARKS: Attended Mon-Thu 1400-2400Z‡, clsd Fri-Sun and hol. See FLIP AP/1 Supplementary Arpt Information.
RSTD 24 hr PPR for ldg and fuel; ctc Base OPS DSN 789-5322, C435-831-5322. All USAF, ANG, and AFRES AMC acft
 consult ASRR for this location. **CAUTION** Ldg short of Rwy 30 is a significant haz. The E-5 barrier protrudes several inches
 abv the grd. Acft ctc with the barrier short of the rwy thld can cause damage to the barrier and substantial damage to the
 acft. Potential for wild animals to cross rwy and foreign object damage haz dur high wind cond. Bird activity monitored
 on req. Limited ARFF capability for manned acft, call BASE OPS for information. **TFC PAT** TPA—Fixed wing 6000(1650),
 Rotary wing 5000(650).
AIRPORT MANAGER: 435-831-5322
COMMUNICATIONS: CTAF 126.2 270.3
RANGE CON 36.1 126.2 270.0 **CLOVER CON SOUTH** 134.1 363.5 **FIRE STATION** 126.2R
CLEARANCE DELIVERY PHONE: For CD ctc Salt Lake ARTCC at 801-320-2568.
RADIO AIDS TO NAVIGATION: NOTAM FILE DPG.
 (T) **TACAN** Chan 79 MIJ (113.2) N40°11.50' W112°55.34' at fld. 4348/13E.
 No NOTAM MP: 1300-1500Z‡ Mon

MILFORD MUNI/BEN AND JUDY BRISCOE FLD (MLF)(KMLF) 2 N UTC-7(-6DT) N38°25.60' LAS VEGAS
 W113°00.80' H-3D, L-9C
 5042 B NOTAM FILE MLF IAP
RWY 16-34: H5004X75 (ASPH) S-26 MIRL 0.3% up S
RWY 16: REIL. PAPI(P2L)—GA 3.0° TCH 40'.
RWY 34: REIL. PAPI(P2L)—GA 3.0° TCH 42'.
SERVICE: **FUEL** 100LL, JET A **LGT** ACTVT REIL Rwy 16 and Rwy 34,
 MIRL Rwy 16-34—CTAF. PAPI Rwy 16 and Rwy 34 on consly.
AIRPORT REMARKS: Unattended. Pilots advise if doing touch and go ldg. Cold
 temperature airport. Altitude correction required at or below -27C.
AIRPORT MANAGER: (435) 463-9565
WEATHER DATA SOURCES: ASOS 135.025 (435) 387-5201.
COMMUNICATIONS: CTAF/UNICOM 122.8
MILFORD RCO 112.1T 122.1R (CEDAR CITY RADIO)
 (R) **SALT LAKE CENTER APP/DEP CON** 125.575
CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Salt Lake
 ARTCC at 801-320-2568.



CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE MLF.

(H) (H) **VORTAC** 112.1 MLF Chan 58 N38°21.62' W113°00.79' 344° 4.0 NM to fld. 4980/16E.
moderate to heavy roughness over mountain ridges 072 radial at 10 nm

VOR portion unusable:

010°-030° byd 35 NM blo 10,400'

030°-040° byd 26 NM blo 10,800'

040°-080° byd 23 NM 13,700'

080°-100° byd 17 NM 12,900'

100°-115° byd 16 NM blo 11,600'

115°-125° byd 22 NM blo 11,600'

235°-275° byd 30 NM blo 11,300'

275°-300° byd 25 NM blo 11,200'

300°-320° byd 30 NM blo 9,300'

TACAN AZIMUTH & DME portion unusable:

010°-030° byd 20 NM blo 15,000'

030°-055° byd 20 NM

055°-065° byd 10 NM

065°-080° byd 10 NM blo 14,000'

065°-080° byd 22 NM

080°-115° byd 10 NM

115°-125° byd 20 NM

225°-240° byd 20 NM blo 16,000'

240°-270° byd 15 NM blo 16,000'

270°-305° byd 20 NM blo 16,000'

305°-320° byd 20 NM blo 12,000'

MOAB

CANYONLANDS RGNL (CNY)(KCNY) 15 NW UTC-7(-6DT) N38°45.46' W109°45.21'

4579 B Class I, ARFF Index A NOTAM FILE CNY

RWY 03-21: H7361X100 (ASPH-GRVD) D-85 PCN 30 F/C/X/T MIRL

RWY 03: REIL. PAPI(P4L)—GA 3.45° TCH 40'.

RWY 21: REIL. PAPI(P4L)—GA 3.0° TCH 40'. Thld dspcd 260'.

P-line. Rgt tfc.

RWY 15-33: 2121X60 (GRVL) 0.7% up NW

RUNWAY DECLARED DISTANCE INFORMATION

RWY 15: TORA-2000 TODA-2000 ASDA-2000 LDA-2000

RWY 33: TORA-2000 TODA-2000 ASDA-2000 LDA-2000

SERVICE: S2 FUEL 100LL, JET A OX 1, 2 LGT ACTVT REIL Rwy 03 and 21; PAPI Rwy 03 and 31; MIRL Rwy 03-21—CTAF. PAPI Rwy 03 and 21 on consly durg dalgt hrs; SS-SR ACTVT CTAF.

AIRPORT REMARKS: Attended Mar-Nov 1400-0200Z†, Dec-Feb 1500-0000Z†. Rwy 15-33 and Twy B clsd to acr opns. Parachute Jumping. Ldg fee.

AIRPORT MANAGER: 435-259-4849

WEATHER DATA SOURCES: ASOS 118.525 (435) 259-8576.

COMMUNICATIONS: CTAF/UNICOM 122.8

MOAB RCO 122.3 (CEDAR CITY RADIO)

® **DENVER CENTER APP/DEP CON** 134.5

RADIO AIDS TO NAVIGATION: NOTAM FILE CDC.

MOAB (T) (T) VOR/DME 109.8 OAB Chan 35 N38°45.37' W109°44.96' at fld. 4542/10E.

VOR unusable:

280°-292° blo 6,700'

280°-295° byd 10 NM

DME unusable:

035°-050° byd 15 NM blo 9,000'

180°-190° byd 15 NM blo 10,000'

DENVER

H-3E, L-9D

IAP

