

LAKE HOOD (LHD)(PALH) P (ANG) 3 SW UTC-9(-8DT) N61°11.20' W149°57.92'

ANCHORAGE
AD

79 TPA—See Remarks NOTAM FILE LHD
RWY 14-32: 2200X75 (GRVL-DIRT) MIRL

RWY 14: Tree.
RWY 32: Tree. Rgt tfc.
SERVICE: S4 **FUEL** 100, 100LL, JET A **LGT** SS-SR.
NOISE: Noise sensitive area in effect, contact arpt manager
 907-266-2741 for further information.

AIRPORT REMARKS: Special Air Traffic Rules-Part 93, see Regulatory Notices. Attended continuously. PPR for non-radio operations. TPA-673(600). No nighttime non-radio acft operations permitted. Ctc FAA at 907-271-5936, request to be transferred to twr. Provide an ETA and remain within plus or minus 15 minutes of ETA. Rwy 14-32 tfc pat overlaps seadrome pat. Fuel avbl at Rwy 14-32 tsnt prkg & FBOs. Numerous water fowl and nesting area invof arpt. Large flocks of migratory birds invof arpt spring to fall. Twy around Lake Hood is a joint use twy/road and is used by motor vehicles/bicyclists/joggers and tour buses. Use of fldg lgt when taxiing recommended. Rwy 14-32 ltd to 9000 lb or less. Public ramps on N and W shore of Lake Hood. Area Southwest and Northwest of Lake Spenard from Canal eastward 1500' not visible from twr. Twy V PCL security gate east of Twy E, key 121.75 5 times to ACTIVATE. Twy H-2, Lakeshore twy gates PCL, Key 121.75 3 times to ACTIVATE. Arr/Dep routes; See Area Notices. See notice in Section C for arpt layout graphic.

AIRPORT MANAGER: 907-266-2741

WEATHER DATA SOURCES: ASOS (907) 245-5432 (WX CAM)
COMMUNICATIONS: CTAF 126.8 ATIS 125.6 (907-245-5432)

Ⓡ **ANCHORAGE APP/DEP CON** 119.1 363.2

TOWER 126.8 (907-245-5432)
CLNC DEL 119.4

AIRSPACE: CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE ANC.

ANCHORAGE (H) (H) VOR/DME 113.15 TED Chan 78(Y) N61°10.07' W149°57.61' 334° 1.1 NM to fld. 93/18E.

VOR unusable:

- 041°-091° byd 25 NM blo 15,000'
- 091°-096° byd 20 NM blo 15,000'
- 096°-121° byd 25 NM blo 12,500'
- 121°-146° byd 25 NM blo 9,000'

DME unusable:

- 041°-091° byd 25 NM blo 15,000'
- 091°-096° byd 20 NM blo 15,000'
- 096°-121° byd 25 NM blo 12,500'
- 121°-146° byd 25 NM blo 9,000'
- 196°-206° byd 25 NM blo 3,500'
- 206°-211° byd 25 NM blo 4,000'
- 211°-221° byd 25 NM blo 3,500'

COMM/NAV/WEATHER REMARKS: For a toll free call to Kenai FSS dial 1-866-864-1737.

WATERWAY E-W: 4541X188 (WATER)

WATERWAY N-S: 1930X200 (WATER)

WATERWAY SE-NW: 1369X150 (WATER)

SEAPLANE REMARKS: All waterlanes elev 76'. North pothole designated no-wake area to protect moored acft/shoreline. Lake clsd to acft over 12,500 lbs from freeze up til approximately Dec 31, overflows into ice may occur winter months. For availability of winter ski ops on lake sfcs, consult local NOTAMS and ctc twr prior to arrival/departure. Floating debris on lake.

