CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 114.0
RADIO AIDS TO NAVIGATION: NOTAM FILE GEG.
SPOKANE (VH) (H) VORTACW 115.5 GEG Chan 102 N47°33.90´ W117°37.61´ 046° 14.2 NM to fld. 2756/14E.
VOR unusable:
007°–022° byd 26 NM blo 7,000´
029°–041° byd 40 NM
307°–337° byd 30 NM blo 9,000´
342°–007° byd 18 NM blo 7,000´
342°–007° byd 25 NM
ILS/DME 111.7 I–FLZ Chan 54 Rwy 22R. Class IB. LOC unusable 0.2 NM fm rwy thld. DME unusable 15° rgt of course.
COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

• • • • • • • • • • • • • • • • • • •

WATERWAY 03W–21W: 6000X100 (WATER)
WATERWAY 21W: Rgt tfc.
SEAPLANE REMARKS: Extv boating in area of water rwy. Water lvl on river may be lwrd by corps of engr. Water area adj to arpt not ctld or mntnd by arpt. Waterway elev 1910 estd. Waterway 03W–21W water rwy advsy svc only area not visible from twr. Ctc Felts twr 132.5 for tfc data.

SPOKANE INTL (GEG)(KGEG) P (ARNG) 5 SW UTC–8(–7DT) N47°37.14´ W117°32.11´ — **SEATTLE H–1C, L–13B IAP, AD**
2385 B LRA Class I, ARFF Index C NOTAM FILE GEG MON Airport
RWY 03–21: H11002X150 (ASPH–CONC–GRVD) S–200, D–200, 2S–175, 2D–400 PCN 88 R/B/W/T HIRL CL
RWY 03: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 69´. RVR–TMR Rgt tfc. 0.5% down.
RWY 21: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 73´. RVR–TMR Ground. 0.6% up.
RWY 08–26: H8199X150 (ASPH–GRVD) S–150, D–180, 2D–280 PCN 40 R/B/X/T MIRL
RWY 08: REIL. PAPI(P4R)—GA 3.0° TCH 45´. Rgt tfc.
RWY 26: REIL. PAPI(P4L)—GA 3.0° TCH 48´.
RUNWAY DECLARED DISTANCE INFORMATION
RWY 03: TORA–11002 TODA–11002 ASDA–11002 LDA–11002
RWY 08: TORA–8199 TODA–8199 ASDA–8199 LDA–8199
RWY 21: TORA–11002 TODA–11002 ASDA–11002 LDA–11002
RWY 26: TORA–8199 TODA–8199 ASDA–8199 LDA–8199
SERVICE: S4 **FUEL** 100, 100LL, JET A **OX** 1, 2, 3, 4 **MILITARY— FUEL** A, A+ (C509–455–5204, avbl 1400–0600Z‡, hol 1600–0000Z‡, OT 2 hr PN, $90 per hr fee) (NC–100, 100LL).



AIRPORT REMARKS: Attended continuously. Waterfowl and birds on and invof arpt. Twy K unlgtd on ramp side along maintenance ramp and is unavbl blo 1200´ RVR unless under escort by "follow me." Portions of Twy K not visible from twr. Rwy 21 ALSF2 may be opr as SSALR during favorable wx conditions. Be alert to turbulence over smoke stacks 1 mile east of arpt. U.S. Customs user fee arpt. Flight Notification Service (ADCUS) avbl.
AIRPORT MANAGER: (509) 455-6418
WEATHER DATA SOURCES: ASOS (509) 742–2544 WSP.
COMMUNICATIONS: ATIS 124.325 509–838–0895 **UNICOM** 122.95
RCO 122.2 (SEATTLE RADIO)
® **APP/DEP CON** 123.75 205°–025° 133.35 26°–204°
TOWER 118.3 **GND CON** 121.9 **CLNC DEL** 127.55
AIRSPACE: CLASS C svc ctc **APP CON**.
VOR TEST FACILITY (VOT) 109.6
RADIO AIDS TO NAVIGATION: NOTAM FILE GEG.
(VH) (H) VORTACW 115.5 GEG Chan 102 N47°33.90´ W117°37.61´ 035° 4.9 NM to fld. 2756/14E.
VOR unusable:
007°–022° byd 26 NM blo 7,000´
029°–041° byd 40 NM
307°–337° byd 30 NM blo 9,000´
342°–007° byd 18 NM blo 7,000´
342°–007° byd 25 NM
ILS/DME 111.1 I–OLJ Chan 48 Rwy 03. Class IIIE.
ILS/DME 111.1 I–GEG Chan 48 Rwy 21. Class IIIE.

STAMPEDE PASS SMP N47°15.98´ W121°22.07´/3964 — **SEATTLE L–1D**
ASOS 135.275 (360) 886–2758