

MAMMOTH YOSEMITE (See MAMMOTH LAKES on page 199)**MARCH ARB** (RIV)(KRIV) MIL/CIV AF 6 SE UTC-8(-7DT) N33°52.92' W117°15.54'

1536 B TPA—See Remarks AOE NOTAM FILE RVR Not insp.

RWY 14-32: H13302X200 (CONC) PCN 58 R/B/W/T HIRL**RWY 14:** PAPI(P4L)—GA 2.59° TCH 56'. RVR—TMR**RWY 32:** ALSF1. PAPI(P4L)—GA 3.0° TCH 59'. RVR—TMR**RWY 12-30:** H3061X100 (ASPH) PCN 20 F/A/W/T**ARRESTING GEAR/SYSTEM****RWY 14 TYPE-H BAK-12B(B)** (1500')TYPE-H BAK-12B(B) (1500') **RWY 32****SERVICE:** S4 **FUEL** 100LL, JET A, A+++ **OX 1, 2, 3, 4 MILITARY—LGT** **Rwy 14** PAPI angle nstd 2.59 deg, TCH 56'. PAPI**Rwy 32** angle 3.0 deg, TCH 59'. **JASU** (MC-2A) (A/M32A-86) (AM32-95) **FUEL** A+++, 100LL Full svc 100LL avbl at FBO.**FLUID** SP LHOX LOX LHNIT **OIL** JOAP avbl on on reserve wknd . O-148. **TRAN ALERT** Opr 1500-0400Z‡ Mon-Sat;

1500-0300Z‡ Sun. Tran acct no practice apch 0500-1500Z‡.

AIRPORT REMARKS: Opr H24; ops fr 0700-1500Z‡ rqr 452 OG/CC avpl, exc for KRIV based alert msn. Rwy 12-30 CLOSED to public use only. Rwy 12-30 CLOSED to public due to munitions and explosives ops in close proximity of Rwy 12-30 per UFC and DOD regulations. Rwy 12-30 is a sry rwy, used for mil ops and mntnd by the mil. It is in very poor cond. Use extreme caution for extensive UAS ops in vicinity. Extv glider, skydiving, balloonist and ultralight activity at Perris Arpt, 7 NM south of March. Heavy mil flt trng. TPA—rectangular Rwy 14-32 3000' (1464'), Rwy 12-30 2500' (964'); overhead Rwy 14-32 3500' (1964'), Rwy 12-30 2500' (964'). Joint use arpt owned and opr by US Air Force/no civil touch and go ops or maneuvers. Aflid use agreement with civil arpt authority (March Inland Port Arpt Authority) mil, civ coml and general aviation (GA) uses. General aviation ops PPR and/or ldg permit not rqr for use of civ apron and ramps. FBO info 951-247-2111/freq 130.075. General aviation ops permitted during FBO BUS HRS. FBO bus hrs 1400-0600Z‡ Mon-Fri, open Sat-Sun (if req prior to close of bus Fri) and will honor medical req made at any time, call 951-247-2111.

MILITARY REMARKS: Attended 1500-0700Z‡, clsd hol. Ops 0700-1500Z‡ and on hol rstd to KRIV based alert msn. General Aviation ops PPR and/or ldg permit not rqr for use of civ apron and ramps. FBO no PPR rqr 1400-0600Z‡ Mon-Fri, clsd weekends, OT ctc FBO C951-247-2111 or C951-203-7797. See FLIP AP/1 Supplementary Arpt Info. 24 hr PN/PPR for all tran acct, ctc aflid mgmt OPS DSN 312-447-4404/2422, C951-655-4404/2422. 24 hr PN acct with PAX/cargo ctc Comd Post DSN 312-447-4665 24 with type cargo and number of PAX. Inbound acct with PAX or DV ctc Comd Post no later than 2 hr prior to ETA and again no later than 1 hr ETA. **RSTD** Rwy 12-30 and helipad not avbl for public use. Rwy 14-32 avbl for public use rstd to full stop ldgs to FBO and straight-in low approach ft permitting. RSRSt rstd Det 1, 144 FW F-16 acct. AMP-3 LZ lgt instl in Rwy 14-32 rstd to 452 AMW acct. Tran acct trns trng rstd when ngt vision devices in use. 180° turns not auth on asphalt portions of Rwy 14-32. 180° turns auth on conc portions of Rwy 14-32. Med to large frame acct not allowed to taxi on Lima prk row w flw me escort. All acct must advs ATC prior to executing a Vis Climb Over Arpt (VCOA). V-22 ops rstd to Rwy 14/32. Helipad and Rwy 12/30 are unsuitable for V-22 ops due to rwy in very poor cond and FOD potential. **CAUTION** Rwy mark-landing zone (LZ) mark(3500'X90') painted on Rwy 32 for base asgn C17 acct only. NSTD cti twr cti LZ lgt instl 300' N of AER 32. NSTD TACAN checkpoint signs located at Twy A and Twy F. **MISC** SRS authorized for Det 144 F/W F16 acct only. Transportation limited, prior coordination rqr, ctc DSN 312-447-7787 wknd. **CSTMS/AG/IMG** Min 24 hr PN rqr, ctc aflid mgmt ops DSN 312-447-4404/2422, C951-655-4404/2422. Ltd svc on call Ontario Intl based CSTMS exp 2 hr delay for no ntc acct acct arr CSTMS rqr. CBP Form 7507 Gen Declaration, CBP form 6059B CSTMS Declaration fr all pax. PAX/cargo manifest rqr as applicable. Crew, PAX, cargo rqr to remain in acct ltd released by CSTMS. Apv Ldg Rights and Ovft Exm req. Not a port of entry, IMG svc ltd, case-by-case basis. Ctc PTD 2 hr prior to ldg via drct A/G com or fone patch. **RWY Rwy 12-30** has extv cracks, vegetation, and loose rocks; Rwy 14 apch end full width conc first 500', flw 110' taper to 75' width conc on cntrln remaining 125' width asphalt. Rwy 32 apch end full width conc first 1000', flw 110' taper to 100' width conc on cntrln remaining 100' width asphalt; twy lead-in 75' width conc.

AIRPORT MANAGER: 951-655-4053**COMMUNICATIONS:** ATIS 134.75 239.05 **PTD** 372.2 (Reception extremely ltd due to high surrounding terrain.)

Ⓡ **APP/DEP CON** 119.25 133.5 306.975 1500-0700Z‡, Sat-Sun 1500-0200Z‡, clsd holidays, other times ctc

Ⓡ **SOCAL APP/DEP** 134.0 278.3

TOWER 127.65 253.5 **GND CON** 121.75 335.8 **CLNC DEL** 335.8452 **OG** 252.1

COMD POST 311.0 321.0 349.4 **PMSV METRO** 239.8 Wx Station 24 hrs, DSN 447-3602, C951-655-3602. Augmented AWOS in use. For additional info or dur evac of wx, ctc the 25th OWS at Davis Monthan AFB, AZ DSN 312-228-6698, C520-228-6698.

LOS ANGELES

COPTER

H-4I, L-4H, A

DIAP, AD

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

AIRSPACE: CLASS C svc ctc APP CON svc Mon–Fri 1500–0700Z†, Sat–Sun 1500–0200Z†, clsd hol; other times CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE RAL.

PARADISE (VH) (H) VORTACW 112.2 PDZ Chan 59 N33°55.10' W117°31.80' 084° 13.7 NM to fld. 1432/15E.

TACAN AZIMUTH unusable:

130°–145° byd 25 NM blo 5,000'
 145°–190° blo 8,000'
 190°–230° blo 10,000'
 310°–325° byd 35 NM blo 10,900'
 325°–345° byd 25 NM blo 11,500'
 345°–360° byd 35 NM blo 10,500'

VOR unusable:

000°–006° byd 40 NM
 007°–017° byd 40 NM blo 10,000'
 007°–017° byd 48 NM
 010°–015° byd 20 NM blo 10,000'
 018°–040° byd 40 NM
 041°–051° byd 40 NM blo 25,000'
 052°–065° byd 40 NM
 080°–088° byd 40 NM
 108°–118° byd 40 NM blo 9,000'
 108°–118° byd 53 NM
 119°–144° byd 40 NM blo 12,000'
 119°–144° byd 85 NM
 130°–145° byd 25 NM blo 5,000'
 145°–190° blo 8,000'
 145°–190° byd 25 NM blo 10,000'
 145°–190° byd 39 NM blo 13,500'
 190°–230° blo 10,000'
 285°–300° byd 40 NM
 301°–311° byd 40 NM blo 18,000'
 310°–325° byd 35 NM blo 10,900'
 325°–345° byd 25 NM blo 11,500'
 345°–360° byd 35 NM blo 10,500'

DME unusable:

130°–145° byd 25 NM blo 5,000'
 145°–190° blo 8,000'
 190°–230° blo 10,000'
 310°–325° byd 35 NM blo 10,900'
 325°–345° byd 25 NM blo 11,500'
 345°–360° byd 35 NM blo 10,500'

HOMELAND (L) VORW 112.05 HDF N33°46.58' W117°11.12' 316° 7.3 NM to fld. 1416/14E.

VOR unusable:

017°–030° byd 35 NM blo 15,500'
 155°–155° byd 24 NM
 190°–207° byd 20 NM

(L) TACAN Chan 77 RIV (113.0) N33°54.39' W117°16.50' 137° 1.7 NM to fld. 1543/14E. NOTAM FILE RIV.

TACAN AZIMUTH unusable:

040°–055° byd 20 NM blo 18,500'
 085°–090° byd 35 NM blo 14,000'
 170°–220° byd 35 NM blo 11,000'
 240°–275° byd 35 NM blo 8,000'
 300°–039° byd 20 NM blo 17,000'

No NOTAM MP 1500–1700Z† Thu (1500/3+1), exc last Thu 1500–2300Z† (1500/3+1)

DME unusable:

040°–055° byd 20 NM blo 18,500'
 085°–090° byd 35 NM blo 14,000'
 170°–220° byd 35 NM blo 11,000'
 240°–275° byd 35 NM blo 8,000'
 300°–039° byd 20 NM blo 17,000'

ILS 110.1 I–RIV Rwy 32. Class IE. No NOTAM MP 0500–0900Z† Wed.

ASR (1500–0700Z†. No–NOTAM MP 0700–1500Z† Wed)