

LAUGHLIN/BULLHEAD INTL (IFP)(KIFP) 1 N UTC-7 N35°09.28' W114°33.56'
 707 B TPA—See Remarks Class I, ARFF Index B NOTAM FILE IFP
RWY 16-34: H8501X150 (ASPH-GRVD) S-75, D-200, 2D-400

PHOENIX
H-4J, L-7E
IAP, AD

PCN 52 F/A/X/T MIRL

RWY 16: REIL. PAPI(P4L)—GA 3.0° TCH 49'. Pole. Rgt tfc. 0.9% up.
RWY 34: REIL. PAPI(P4L)—GA 3.0° TCH 45'. 1.0% down.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 16: TORA-8500 TODA-8500 ASDA-8500 LDA-8500
RWY 34: TORA-8500 TODA-8500 ASDA-8500 LDA-8500

SERVICE: FUEL 100LL, JET A **OX 1, 2** **LGT** ACTVT REIL Rwy 16-34;
 MIRL Rwy 16-34—CTAF.

NOISE: Noise sensitive areas NE and SE of arpt.

AIRPORT REMARKS: Attended continuously. Svcs and fuel

1300-0500Z-122.85; aft hr not avbl. Sfc cond unmnt 0600Z-1200Z.
 Ctn: lrg coml ops aft ATCT hrs; birds on and invof arpt Sep-Dec. Radar
 svc blw 6000 ft. not avbl. Twy Alpha 4 ltd to wingspans less than 79
 ft. Twy A5 btn Twy A and gen avn apron ltd to wingspan less than 79
 ft. Mountains NW, NE, E, and SE. Rising trrn N and S of rwy ends. Rwy
 16 66 ft pline parl to rwy 625 ft L 1300 ft fm rwy end. TPA for light
 acct 1706(999), TPA for high performance acct 2206(1499). GA Indg
 fee—928-754-2134.

AIRPORT MANAGER: 928-754-2134 X24

WEATHER DATA SOURCES: AWOS-3PT 119.825 (928) 754-4462.

COMMUNICATIONS: CTAF 123.9 ATIS 119.825 (1500-0100Z)

® **L.A. CENTER APP/DEP CON** 134.65

BULLHEAD TOWER 123.9 (1500-0100Z) **GND CON** 118.25

L.A. CENTER CLNC DEL 118.25 (When tower closed)

AIRSPACE: CLASS D svc 1500-0100Z; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE EED.

NEEDLES (VH) (H) VORTAC 115.2 EED Chan 99 N34°45.96' W114°28.45' 335° 23.7 NM to fld. 620/15E.

VOR unusable:

- 042°-052° byd 40 NM blo 18,000'
- 053°-059° byd 40 NM
- 060°-070° byd 40 NM blo 18,000'
- 071°-085° byd 40 NM blo 10,000'
- 071°-085° byd 55 NM
- 095°-110° byd 40 NM
- 100°-130° byd 27 NM blo 6,600'
- 170°-220° byd 20 NM blo 5,800'
- 211°-221° byd 40 NM blo 14,500'
- 211°-221° byd 66 NM
- 220°-280° byd 35 NM blo 6,800'
- 222°-251° byd 40 NM
- 252°-262° byd 40 NM blo 8,000'
- 252°-262° byd 62 NM
- 263°-281° byd 40 NM
- 289°-309° byd 40 NM
- 319°-326° byd 40 NM
- 335°-041° byd 40 NM

TACAN AZIMUTH unusable:

- 100°-130° byd 27 NM blo 6,600'
- 165°-220° byd 20 NM blo 8,000'
- 165°-220° byd 30 NM blo 12,000'
- 170°-220° byd 20 NM blo 5,800'
- 220°-280° byd 35 NM blo 6,800'

DME unusable:

- 100°-130° byd 27 NM blo 6,600'
- 165°-220° byd 20 NM blo 8,000'
- 165°-220° byd 30 NM blo 12,000'
- 170°-220° byd 20 NM blo 5,800'
- 220°-280° byd 35 NM blo 6,800'

COMM/NAV/WEATHER REMARKS: ATIS broadcasts during tower hours of operation. After tower hours of operation broadcast will revert to AWOS-3PT using the same frequency.

