OREGON

197

```
PORTLAND-HILLSBORO (HIO)(KHIO)
                                     15 SW UTC-8(-7DT) N45°32.53′ W122°57.04′
                                                                                                         SFATTLE
208 B TPA-See Remarks LRA NOTAM FILE HIO MON Airport
                                                                                                      H-1B I-1C
RWY 13R-31L: H6600X150 (ASPH) S-50, D-70, 2D-110 HIRL
                                                                                                          IAP, AD
   RWY 13R: MALSR, PAPI(P4L)-GA 3.0° TCH 49', RVR-T
   RWY 31L: REIL. PAPI(P4L)-GA 3.0° TCH 51'. Tree.
RWY 02-20: H3820X75 (ASPH) S-54.5, D-74, 2D-139 PCN 20 F/C/X/T MIRL
   RWY 02: PAPI(P4R)—GA 3.0° TCH 39', Road, Rgt tfc.
   RWY 20: PAPI(P4L)-GA 3.0° TCH 38'. Tree.
RWY 13L-31R: H3600X60 (ASPH) S-28 PCN 10 F/D/Y/T MIRL
   RWY 13L: PAPI(P4L)—GA 3.0° TCH 27'.
   RWY 31R: PAPI(P4L)-GA 3.0° TCH 26'. Rgt tfc.
LAND AND HOLD-SHORT OPERATIONS
  I DG RWY
                    HOLD-SHORT POINT
                                                AVRI I DG DIST
   RWY 13R
                    02-20
                                                4922
SERVICE: S4 FUEL 100LL, JET A 0X 1, 2, 4 LGT When twr clsd ACTVT MALSR Rwv 13R: PAPI Rwv 02 and PAPI Rwv
   20—CTAF. Rwy 13L PAPI unusbl beyond 8 deg L and R of rwy cntrln. Rwy 31R PAPI unusbl beyond 8 deg L and R of
NOISE: NS ABTMT procedures in effect call 503-460-4100 or 800-938-6647. Noise sensitive areas border arpt west, south
   and east, Rwy 31L is preferred rwy for NS ABTMT. Avoid low level over flts of residential areas whenever possible.
   Nighttime touch and gos are discouraged 0600-1400Z‡.
AIRPORT REMARKS: Attended 1400-0600Z‡. Rwy 13R-31L clsd to touch and go ldgs between 0600-1400Z‡. Be alert for
   bird act in vicinity Nov to May. Glider ops 5 NM northwest during dalgt hrs Mar-Oct. TPA-1208 (1000), turbine and
   large acft 1708 (1500). Rwy 13R run-up area not visible from twr. Rwy 02-20 has 150' x 75' paved blast pads at both
   ends. Rwy 13R-31L has 200' x 150' paved blast pads at both ends. Be alert, extv helicopter training operations to Twy
   A, Twy B & Twy D. Flight Notification Service (ADCUS) avbl, 2 hr advance ntc rgr Mon-Sat 0100-1400Z‡ and 24 hrs
   Sun and hol. ComI acft and oprs of acft with an FAA certified maximum gross ldg weight that exceeds 10,000 lbs are rqr
   to pay a ldg fee. Ldg fee. Fee based cstms facility $60 single engine, $175 twin engine, $500 turbine. Cstms avbl
   2000-0400Z‡ 503-693-1069, otherwise cstms Flt Notification (ADCUS) avbl, advance coordination rgr
   503-326-3230. NOTE: See Special Notices—Intensive Flight Training Advisory. See Special Notices—Arrival Alert.
AIRPORT MANAGER: 503-460-4119
WEATHER DATA SOURCES: ASOS (503) 615-4314
COMMUNICATIONS: CTAF 119.3 ATIS 127.65 UNICOM 122.95
® APP/DEP CON 126.0 269.175 (LOW) 118.1 284.6 (HIGH)
   TOWER 119 3 (1400-06007±) GND CON 121 7
CLEARANCE DELIVERY PHONE: For CD when twr clsd ctc Portland Apch at 503-493-7545.
AIRSPACE: CLASS D svc 1400-0600Z‡; other times CLASS E.
VOR TEST FACILITY (VOT) 115.2
RADIO AIDS TO NAVIGATION: NOTAM FILE MMV.
   NEWBERG (VH) (DH) VORW/DME 117.4 UBG Chan 121 N45°21.19′ W122°58.69′ 345° 11.4 NM to fld.
     1443/21F
   VOR unusable:
     095°-105° bvd 40 NM
     106°-120° byd 40 NM blo 7,800′
     106°-120° byd 60 NM
     135°-328° bvd 40 NM
     329°-346° byd 40 NM blo 5,000′
     329°-346° byd 70 NM
     347°-080° byd 40 NM
   BANKS NDB (MHW) 356 PND N45°37.82′ W123°02.75′ 127° 6.6 NM to fld. 211/16E. NOTAM FILE HIO.
   ILS 110.7 I-HIO Rwy 13R. Class IE. Unmonitored when ATCT clsd. Localizer unusable beyond 27° each side of
COMM/NAV/WEATHER REMARKS: Emerg freq 121.5 not avbl at twr.
```