

SPOKANE

FELTS FLD (SFF)(KSFF) 4 NE UTC-8(-7DT) N47°40.98' W117°19.35'

SEATTLE
L-13B
IAP, AD

1957 B LRA NOTAM FILE SFF
RWY 04L-22R: H4499X140 (CONC) S-30 MIRL
RWY 04L: REIL. VASI(V2L)—GA 3.0° TCH 50'.
RWY 22R: MALSR. VASI(V2R)—GA 3.5° TCH 44'. Tree. Rgt tfc.
RWY 04R-22L: H2650X75 (ASPH) S-30
RWY 04R: Rgt tfc.
RWY 22L: PAPI(P4L)—GA 3.8° TCH 39'. Tree.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04L: TORA-4499	TODA-4499	ASDA-4499	LDA-4499
RWY 04R: TORA-2650	TODA-2650	ASDA-2650	LDA-2650
RWY 22L: TORA-2650	TODA-2650	ASDA-2650	LDA-2650
RWY 22R: TORA-4499	TODA-4499	ASDA-4499	LDA-4499

SERVICE: S4 FUEL 100LL, JET A1+ OX 3, 4 LGT When twr clsd
 ACTIVATE MIRL Rwy 04L-22R, MALSR Rwy 22R and REIL 04L-CTAF.
 VASI Rwy 04L and VASI Rwy 22R opr continuously. PAPI Rwy 22L opr
 SR-SS. Rwy 22L PAPI unusable byd 5° right side of cntrln.

AIRPORT REMARKS: Attended 1400-0400Z±. Waterfowl and birds on and
 in vof arpt. Lgtd crane 1953' MSL (200' AGL) 1.25 NM east indef. Acft
 with tail heights over 20' must ctc twr prior to taxi. Twr unable to
 provide ATC svc on perimeter twy due to movement of unclt gnd tfc.
 Portions of Twy B not visible from twr. PPR for rotorwing acft conducting
 hover ops above 10' AGL in non-movement area ctc twr. Cold temperature airport. Altitude correction required at or below
 -16C. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 509-455-6418

WEATHER DATA SOURCES: ASOS 120.55 (509) 535-3290.

COMMUNICATIONS: CTAF 132.5 ATIS 120.55 UNICOM 122.95

SPOKANE RCO 122.6 (SEATTLE RADIO)

Ⓡ **SPOKANE APP/DEP CON** 133.35

TOWER 132.5 (1400-0400Z±) **GND CON** 121.7 **CLNC DEL** 121.7

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Seattle ARTCC at 253-351-3694.

AIRSPACE: CLASS D svc 1400-0400Z±; other times CLASS E.

VOR TEST FACILITY (VOT) 114.0

RADIO AIDS TO NAVIGATION: NOTAM FILE GEG.

SPOKANE (VH) (H) VORTACW 115.5 GEG Chan 102 N47°33.90' W117°37.61' 046° 14.2 NM to fld. 2756/14E.

VOR unusable:

007°-022° byd 26 NM blo 7,000'

029°-041° byd 40 NM

307°-337° byd 30 NM blo 9,000'

342°-007° byd 18 NM blo 7,000'

342°-007° byd 25 NM

ILS/DME 111.7 I-FLZ Chan 54 Rwy 22R. Class IB. LOC unusable 0.2 NM fm rwy thld. DME unusable 15° rgt of course.

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

WATERWAY 03W-21W: 6000X100 (WATER)

WATERWAY 21W: Rgt tfc.

SEAPLANE REMARKS: Extv boating in area of water rwy. Water lvl on river may be lwrld by corps of engr. Water area adj to arpt
 not ctld or mntnd by arpt. Waterway elev 1910 estd. Waterway 03W-21W water rwy advsy svc only area not visible from
 twr. Ctc Felts twr 132.5 for tfc data.

