

CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 113.9

RADIO AIDS TO NAVIGATION: NOTAM FILE LAX.

(VH) (H) VORTACW 113.6 LAX Chan 83 N33°55.99' W118°25.92' 050° 1.3 NM to fld. 185/15E.

VOR unusable:

- 004°-014° byd 40 NM blo 12,000'
- 004°-014° byd 51 NM
- 015°-053° byd 40 NM
- 060°-081° byd 40 NM blo 4,500'
- 060°-081° byd 58 NM blo 14,000'
- 060°-081° byd 65 NM
- 082°-101° byd 40 NM
- 109°-115° byd 40 NM
- 138°-155° byd 40 NM
- 175°-205° byd 10 NM blo 3,000'
- 270°-277° byd 25 NM blo 8,000'
- 276°-329° byd 40 NM
- 277°-300° byd 10 NM blo 8,000'
- 277°-300° byd 28 NM blo 12,000'
- 341°-003° byd 40 NM

ILS/DME 108.5 I-UWU Chan 22 Rwy 06L. Class IE. Uses I-OSS Rwy 24R DME. Autopilot cpd apch NA blw 503' MSL.

ILS/DME 111.7 I-GPE Chan 54 Rwy 06R. Class IE. Rwy 24L HQB DME used.

ILS/DME 111.1 I-IAS Chan 48 Rwy 07L. Class ID. DME also serves Rwy 25R. DME unusable byd 25° left of course. Autopilot cpd apch NA blw 925' MSL.

ILS/DME 109.9 I-MKZ Chan 36 Rwy 07R. Class IT. DME also serves LAX ILS Rwy 25L

ILS/DME 111.7 I-HQB Chan 54 Rwy 24L. Class IE. DME also serves Rwy 06R.

ILS/DME 108.5 I-OSS Chan 22 Rwy 24R. Class IIIE. DME also used by I-UWU Rwy 06L.

ILS/DME 109.9 I-LAX Chan 36 Rwy 25L. Class IIIE. DME also serves MKZ ILS Rwy 7R

ILS/DME 111.1 I-CFN Chan 48 Rwy 25R. Class IE. DME also serves Rwy 07L.

COMM/NAV/WEATHER REMARKS: LAX scv Txl K and Txl L LAWA ramp twr opn ctc LAWA ramp twr 131.075. LAX scv Txl M LAWA ramp twr opn ctc LAWA ramp twr 131.975.

WHITEMAN (WHP)(KWHP) 1 E UTC-8(-7DT) N34°15.56' W118°24.81'

LOS ANGELES

1003 B NOTAM FILE WHP

COPTER

RWY 12-30: H4120X75 (ASPH) S-12.5 MIRL 1.0% up NW

L-3E, 4G, 7B, A

RWY 12: REIL. PAPI(P2R)—GA 3.8° TCH 54'. Thld dsplcd 729'.

IAP, AD

P-line.

RWY 30: REIL. PAPI(P2L)—GA 3.8° TCH 26'. Thld dsplcd 478'.

P-line. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 12: TORA-3442 TODA-4120 ASDA-3910 LDA-3181

RWY 30: TORA-3191 TODA-4120 ASDA-3940 LDA-3462

SERVICE: S4 FUEL 100LL, JET A OX 1, 3 LGT When twr clsd, arpt lgtc opr continuously. Rwy 12 PAPI does not prvd obstn clnc byd 5 NM from thld.

AIRPORT REMARKS: Attended continuously. Birds on and invof arpt.

Helicopter ops 2500' MSL (1500' AGL) and below. Arpt CLOSED to helicopter training/pattern opr 0400-1600Z†. Dirt infield areas.

Helicopters advised to use care to prevent blasting dirt and debris onto movement areas. Voluntary curfew in efct. All acft oprs, excp for flts related to emerg, lifesaving, firefighting, law enforcement, govt agencies, and svcs to the public such as news media, are reqd to avoid conducting acft arrs and deps btn 0600Z† and 1400Z† daily.

AIRPORT MANAGER: 818-896-5271

WEATHER DATA SOURCES: AWOS-3PT 132.1 (818) 899-9820.


COMMUNICATIONS: CTAF 135.0 ATIS 132.1 818-899-9820

UNICOM 122.95

® SOCAL APP/DEP CON 120.4 (VNY 280°-BUR 050°, North) 134.2 (160°-280° VNY, West)

TOWER 135.0 (1600-0400Z†) GND CON 125.0

CLEARANCE DELIVERY PHONE: For CD when ATCT clsd ctc SoCal Apch at 800-448-3724.



CONTINUED ON NEXT PAGE

