

SAN FRANCISCO INTL (SFO)(KSFO) P (CG) 8 SE UTC-8(-7DT) N37°37.13' W122°22.53'
 13 B LRA Class I, ARFF Index E NOTAM FILE SFO **SAN FRANCISCO**
H-3B, L-2F, 3B, A
IAP, AD

RWY 10L-28R: H11870X200 (ASPH-GRVD) S-75, D-200, 2D-400, 2D/2D2-877 PCN 80 F/B/X/T
 HIRL CL
RWY 10L: REIL. PAPI(P4L)—GA 3.0° TCH 80'. RVR-TMR Tower.
RWY 28R: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 68'. RVR-TMR Thld dsplcd 300'. Rgt tfc.
RWY 10R-28L: H11381X200 (ASPH-GRVD) S-75, D-200, 2D-400, 2D/2D2-877 PCN 80 F/B/X/T HIRL CL
RWY 10R: PAPI(P4L)—GA 3.0° TCH 68'. RVR-TMR Tower. Rgt tfc.
RWY 28L: MALSR. PAPI(P4L)—GA 2.85° TCH 67'. RVR-TMR Thld dsplcd 300'.
RWY 01R-19L: H8650X200 (ASPH-GRVD) S-75, D-200, 2D-400, 2D/2D2-877 PCN 100F/B/X/T HIRL CL
RWY 01R: REIL. RVR-TMR Thld dsplcd 560'. Tree.
RWY 19L: MALSF. TDZL. PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR
RWY 01L-19R: H7650X200 (ASPH-GRVD) S-75, D-200, 2D-400, 2D/2D2-877 PCN 90 F/B/X/T HIRL CL
RWY 01L: REIL. RVR-TMR Thld dsplcd 640'.
RWY 19R: PAPI(P4L)—GA 3.15° TCH 58'. RVR-TMR

RUNWAY DECLARED DISTANCE INFORMATION
RWY 01L:TORA-7650 TODA-7650 ASDA-7650 LDA-7010
RWY 01R:TORA-8650 TODA-8650 ASDA-8650 LDA-8090
RWY 10L:TORA-11870 TODA-11870 ASDA-11193 LDA-11193
RWY 10R:TORA-11381 TODA-11381 ASDA-10704 LDA-10704
RWY 19L:TORA-8650 TODA-8650 ASDA-8650 LDA-8650
RWY 19R:TORA-7650 TODA-7650 ASDA-7650 LDA-7650
RWY 28L:TORA-11381 TODA-11381 ASDA-10981 LDA-10275
RWY 28R:TORA-11870 TODA-11870 ASDA-11870 LDA-11236

ARRESTING GEAR/SYSTEM
RWY 01L: EMAS
RWY 01R: EMAS
RWY 19L: EMAS
RWY 19R: EMAS

SERVICE: FUEL 100LL, JET A, A++ OX3, 4 MILITARY— A-GEAR Rwy 01L EMAS 413 x 227, Rwy 19R EMAS 437 x 227,
 Rwy 01R EMAS 409 x 227, Rwy 19L EMAS 373 x 227. FUEL (100LL, A).
NOISE: Noise sensitive arpt. For noise abatement procedures ctc arpt noise office Monday-Friday 1600-0100Z† by calling
 650-821-5100. NOTE: See Special Notices—Special Noise Abatement Procedures—Preferential Runways.

AIRPORT REMARKS: Attended continuously. Rwy 1L CLOSED to departing Trijet acft with wingspan greater than 155'. PAEW
 AER 28L, Rwy 28R and Rwy 19L indef. Flocks of birds feeding along shoreline adjacent to arpt, on occasions fly across
 various parts of arpt. Due to obstructed vision, SFO twr is able to provide only limited arpt tfc ctl svc on Twy A between
 gates 88 and 89. Twr personnel are unable to determine whether this area is clear of tfc or obstructions. Due to obstd
 vision, the twr is una to dtm if acft pulling into gate F11 are at the hook-up spot or in the gate. Due to obstd vision, SFO
 twr is able to prvd only ltd arpt tfc ctl svc on Twy A btn gates F20 and F21. Rwy 10 preferred rwy between 0900-1400Z†
 wx and flt conditions permitting. ASSC in use. Operate transponders with altitude reporting mode and ADS-B (if equipped)
 enabled on all airport surfaces. Simultaneous ops in effect all rwsys. Airline pilots shall strictly follow the painted nose gear
 lines and no oversteering adjustment is permitted. All obud Twy Zulu 2 heavy acft with a wingspan of 171 ft or gtr under
 pwr prohibited from entering wb Twy Zulu. Twy S btn Twy Z and Twy S2 clsd to acft with wingspan over 215 ft. Rwy status
 lgts in operation. Ldg fee. Flight Notification Service (ADCUS) available. NOTE: See Special Notices—Special Noise
 Abatement Procedures—Preferential Runways.

AIRPORT MANAGER: 650-821-5000
WEATHER DATA SOURCES: ASOS (650) 827-8593 LLWAS.
COMMUNICATIONS: D-ATIS 118.85 115.8 113.7 650-821-0677/1677/2677 UNICOM 122.95
 (R) NORCAL APP CON 120.9 135.1 128.325
 TOWER 120.5 GND CON 121.8 CLNC DEL 118.2 PRE TAXI CLNC 118.2
 (R) NORCAL DEP CON 128.325 133.95 134.5 135.1 (SE-W) 120.9 (NW-E)
 CPDLC (LOGON KUSA)
 PDC
AIRSPACE: CLASS B See VFR Terminal Area Chart.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 111.0

RADIO AIDS TO NAVIGATION: NOTAM FILE SFO.

(VL) (L) VORW/DME 115.8 SFO Chan 105 N37°37.17' W122°22.43' at fld. 6/17E.

VOR unusable:

025°-065° byd 30 NM blo 18,000'
 035°-055° byd 12 NM blo 6,500'
 121°-281° byd 40 NM
 135°-260° byd 10 NM blo 4,500'
 260°-295° byd 35 NM blo 3,000'
 282°-292° byd 40 NM blo 6,000'
 282°-292° byd 46 NM
 293°-336° byd 40 NM
 295°-330° byd 20 NM blo 8,000'
 337°-348° byd 40 NM blo 8,000'
 337°-348° byd 80 NM
 355°-102° byd 40 NM

DME unusable:

025°-065° byd 30 NM blo 18,000'
 035°-055° byd 12 NM blo 6,500'
 150°-190° byd 25 NM blo 4,500'
 190°-260° byd 10 NM blo 4,500'
 260°-295° byd 35 NM blo 3,000'
 295°-330° byd 20 NM blo 8,000'

ILS/DME 108.9 I-SIA Chan 26 Rwy 19L. Class IE. Ry 19L glideslope deviations are possible when critical areas are not required to be protected. Acft operating invof glideslope transmitter. Pilots should be alert for momentary localizer course excursions due to LARGE aircraft operating in vicinity of localizer antenna.

ILS/DME 109.55 I-SFO Chan 32(Y) Rwy 28L. Class IIE.

ILS/DME 111.7 I-GWQ Chan 54 Rwy 28R. Class IIIE.

SAN GABRIEL VALLEY (See EL MONTE on page 150)
