

PHOENIX SKY HARBOR INTL (PHX)(KPHX) P (ANG) 3 E UTC-7 N33°26.06' W112°00.70'

PHOENIX

1135 B TPA—See Remarks LRA Class I, ARFF Index D NOTAM FILE PHX

H-4J, L-5B, A

RWY 08-26: H11489X150 (CONC-GRVD) S-30, D-200, 2S-175, 2D-455, 2D/2D2-965

IAP, AD

PCR 846 R/A/W/T HIRL

RWY 08: MALSF. PAPI(P4L)—GA 3.0° TCH 69'. Thld dsplcd 898'. Blgd.

RWY 26: REIL. PAPI(P4L)—GA 3.0° TCH 71'. Road. Rgt tfc.

RWY 07L-25R: H10300X150 (CONC-GRVD) S-30, D-235, 2S-175, 2D-435, 2D/2D2-940 PCR 674 R/A/W/T HIRL

RWY 07L: MALSR. PAPI(P4L)—GA 3.0° TCH 73'. RVR-T Pole. Rgt tfc.

RWY 25R: PAPI(P4L)—GA 3.0° TCH 70'. RVR-R Antenna.

RWY 07R-25L: H7800X150 (CONC-GRVD) S-30, D-200, 2S-175, 2D-400, 2D/2D2-1010 PCR 796 R/A/W/T HIRL

RWY 07R: MALSR. PAPI(P4L)—GA 3.0° TCH 70'. Pole.

RWY 25L: MALSR. PAPI(P4L)—GA 3.0° TCH 66'. Antenna.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 07L:TORA-10300 TODA-10300 ASDA-10300 LDA-10300

RWY 07R:TORA-7800 TODA-7800 ASDA-7800 LDA-7800

RWY 08: TORA-11489 TODA-11489 ASDA-11489 LDA-10591

RWY 25L:TORA-7800 TODA-7800 ASDA-7800 LDA-7800

RWY 25R:TORA-10300 TODA-10300 ASDA-10300 LDA-10300

RWY 26: TORA-11489 TODA-11489 ASDA-11489 LDA-11489

SERVICE: S4 FUEL 100LL, JET A OX 1, 2, 3, 4 MILITARY— JASU 1(MD-3M) 1(MA-1A) FUEL J4-Ltd supply (MIL), A+ (C602-273-3770.) (NC-100LL, A) FLUID LPOX LOX OIL O-148 (Mil)

NOISE: Noise abatement proc in efct. Eng runs NA wo prior coord with airside ops.

AIRPORT REMARKS: Attended continuously. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. TPA—2135(1000) lgt acft and non-turbo jets; 2635(1500) heavy acft and turbojets. Twy R & ptns of Twy S & T blw ATCT are non vsb fm ATCT. Twy R ovhd train bridge at midpt prvds 82 ft 4 in clnc. Txl Y3 ovhd train bridge at midpt 44 ft 7 in clnc. Twy C btn S & R, D btn D8 & T, D9, H btn Twy H4 & Twy H7, H5, H6, H7 clsd to acft wingspan gtr than 171 ft. Twy A btn A3 & A10, A4, A5, A6, A7, A8, A9, A12, F btn G2 & G3, D13 clsd to wingspan gtr than 135 ft. Twy D btn S and D13, D10, D11, D12 clsd to acft wingspan more than 118 ft. Experimental or gnd dmnstn NA wo prior apvl - airside ops. ANG: offl bus only; bash phase II in eff 1 Mar thru 31 May & 1 Aug thru 31 Oct; ltd ramp space avbl; FBO-602-273-3770. PPR wingspan 215 ft or gtr Group VI - arpt ops 602-273-2008 for follow me svc tax to & fm ramp & rwsys. Prac inst apchs, stop & taxi back Indg, stop & go Indg, tgl NA. Otr flight trng ops NA wo prior written apvl - airside ops 602-273-2008. Intl ldg rights rqr U.S. Cust & Border Protection notification 48 hrs prior to Indg. Intl gate use rqr cdn with arpt ops 48 hr prior to arr. Review hot spot info on arpt diagram. General aviation should ctc arpt mgr 602-273-3300 as to how to view/review arpt video. Rwy status lgts in oprn. Gen info - 602-273-3302. Ldg fee: ovngt prkg fee. Fee for charters, travel club & revenue producing acft. Flight Notification Service (ADCUS) available.

AIRPORT MANAGER: 602-273-3302

WEATHER DATA SOURCES: ASOS (602) 231-8557 TDWR.

COMMUNICATIONS: D-ATIS 127.575

RCO 122.2 (PRESCOTT RADIO)

① **APP/DEP CON** 124.1 (119°-138° 7500' -14,500') (192°-263° 7500' -12,500') 119.2 (319°-057° 7500' and abv) 120.7 (319°-057° blo 7500') 123.7 (119°-138° blo 7500') (139°-191° blo 8500') 124.9 (058°-118° blo 10,500') 126.8 (058°-118° 10,500' and abv) (119°-138° abv 14,500') (139°-191° 8500' and above) (192°-263° abv 12,500') 128.65 (340°-079° abv 5,500') 126.375

TOWER 118.7 (Rwy 08-26) 120.9 (Rwy 07R-25L and Rwy 07L-25R) **GND CON** 119.75 (North) 132.55 (South)

CLNC DEL 118.1

CPDLC (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

CONTINUED ON NEXT PAGE

CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 109.0

RADIO AIDS TO NAVIGATION: NOTAM FILE PRC.

(VH) (H) VORTACW 115.6 PXR Chan 103 N33°25.98' W111°58.21' 260° 2.1 NM to fld. 1184/12E.

VOR unusable:

000°-015° byd 33 NM blo 11,000'
 015°-034° byd 33 NM blo 10,000'
 015°-034° byd 60 NM blo 11,000'
 015°-034° byd 66 NM blo 16,000'
 035°-060° byd 40 NM blo 13,000'
 061°-067° byd 40 NM
 068°-088° byd 40 NM blo 14,000'
 068°-088° byd 60 NM
 090°-100° byd 15 NM blo 8,000'
 090°-117° byd 40 NM
 118°-141° byd 40 NM blo 9,000'
 118°-141° byd 65 NM blo 10,000'
 118°-141° byd 73 NM
 185°-190° byd 30 NM blo 8,000'
 185°-190° byd 38 NM blo 9,000'
 190°-230° byd 20 NM blo 10,000'
 231°-282° byd 40 NM
 318°-320° byd 40 NM
 323°-350° byd 40 NM blo 14,000'
 345°-000° byd 33 NM blo 10,000'
 345°-034° byd 10 NM blo 6,000'

TACAN AZIMUTH unusable:

000°-015° byd 33 NM blo 11,000'
 015°-034° byd 33 NM blo 10,000'
 090°-100° byd 15 NM blo 8,000'
 185°-190° byd 30 NM blo 8,000'
 185°-190° byd 38 NM blo 9,000'
 190°-230° byd 20 NM blo 10,000'
 345°-000° byd 33 NM blo 11,000'
 345°-034° byd 10 NM blo 6,000'
 345°-034° byd 20 NM blo 8,000'

DME unusable:

000°-015° byd 33 NM blo 11,000'
 015°-034° byd 33 NM blo 10,000'
 090°-100° byd 15 NM blo 8,000'
 185°-190° byd 30 NM blo 8,000'
 185°-190° byd 38 NM blo 9,000'
 190°-230° byd 20 NM blo 10,000'
 215°-315°
 345°-000° byd 33 NM blo 11,000'
 345°-034° byd 10 NM blo 6,000'
 345°-034° byd 20 NM blo 8,000'

VOR unusable:

345°-034° byd 20 NM blo 8,000'
 351°-359° byd 40 NM blo 12,000'

ILS/DME 111.5 I-PHX Chan 52 Rwy 07L. Class IE.

ILS/DME 110.75 I-AHA Chan 44(Y) Rwy 07R. Class ID. DME also serves RJG ILS Rwy 25L.

ILS/DME 111.75 I-SYQ Chan 54(Y) Rwy 08. Class IB. LOC unusable 25° left of course. Autopilot coupled apch not applicable blw 1,307' MSL (0.3 NM).

ILS/DME 110.75 I-RJG Chan 44(Y) Rwy 25L. Class IT. DME also serves AHA ILS Rwy 7R.

ILS/DME 111.75 I-CWJ Chan 54(Y) Rwy 26. Class IB.