

JANESVILLE

SOUTHERN WISCONSIN RGNL (JVL)(KJVL) 3 SW UTC-6(-5DT) N42°37.22' W89°02.49'

808 B ARFF Index—See Remarks NOTAM FILE JVL

RWY 14-32: H7302X150 (CONC-GRVD) S-112, D-147, 2S-175, 2D-255 PCR 440 R/B/X/T HIRL

RWY 14: REIL. PAPI(P4L)—GA 3.0° TCH 55'.

RWY 32: MALSR. VASI(V4L)—GA 3.0° TCH 51'.

RWY 04-22: H6701X150 (ASPH-GRVD) S-44, D-60, 2S-165, 2D-105 PCR 170 R/D/X/T HIRL

RWY 04: MALSR. PAPI(P4L)—GA 3.0° TCH 54'.

RWY 22: REIL. PAPI(P4L)—GA 3.0° TCH 45'. Tree.

RWY 18-36: H5004X75 (ASPH) S-37, D-58, 2D-104 PCR 130 F/C/X/T MIRL

RWY 18: Road.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04: TORA-6701 TODA-6701 ASDA-6701 LDA-6701

RWY 14: TORA-7302 TODA-7302 ASDA-7302 LDA-7302

RWY 18: TORA-5004 TODA-5004 ASDA-5004 LDA-5004

RWY 22: TORA-6701 TODA-6701 ASDA-6701 LDA-6701

RWY 32: TORA-7302 TODA-7302 ASDA-7302 LDA-7302

RWY 36: TORA-5004 TODA-5004 ASDA-5004 LDA-5004

SERVICE: S4 FUEL 100LL, JET A LGT ACTIVATE MALSR Rwy 04 & 32; REIL Rwy 14 & 22; VASI Rwy 32; HIRL Rwy 04-22 & 14-32; MIRL Rwy 18-36—CTAF. When twr clsd HIRL Rwy 04-22 preset on low intst; incr intst—CTAF. PAPI Rwy 04, 14, & 22 opr consly.

AIRPORT REMARKS: Attended 1300-2130Z†. Conds not monitored Mon-Fri 2130-1300Z†, Sat, Sun or fed hols. Class IV, ARFF Index A. Clsd to skedd acf ops gtr than 9 psgr seats. Unskedd acf opns gtr than 30 psgr seats; 90 day PPR —call amgr. Rwy 18-36 not avbl for unskd acf at least 31 psgr seats. Lgt sport acft with cruise speed of 60 mph or less enter tfc pat at 500' AGL. Rwy 32 and Rwy 36 apch ends are closely aligned, verify correct rwy and compass heading prior to dep. Rwy 04-22 aprons and ramps rstd to 155 DTW gross wt.

AIRPORT MANAGER: 608-757-5768

WEATHER DATA SOURCES: AWOS-3 (608) 758-1723 LAWRS (1200-0300Z†).

COMMUNICATIONS: CTAF 118.8 ATIS 128.25 UNICOM 122.95

® **ROCKFORD APP/DEP CON** 121.0

JANESVILLE TOWER 118.8 (1200-0300Z†) **GND CON** 121.65 **CLNC DEL** 121.65

CLNC DEL 121.65 (when twr clsd)

AIRSPACE: CLASS D svc 1200-0300Z†; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE JVL.

JANESVILLE (L) VOR/DME 114.3 JVL Chan 90 N42°33.48' W89°06.32' 034° 4.7 NM to fld. 932/3E.

VOR unusable:

001°-089°

155°-175° byd 15 NM

282°-000° byd 30 NM blo 3,000'

ILS 109.1 I-JVL Rwy 04. Class IE. Unmonitored when ATCT clsd.

ILS/DME 111.35 I-REE Chan 50(Y) Rwy 32. Class IE. Unmonitored when ATCT clsd. LOC unusable byd 19° right of course.

JOHN F KENNEDY MEML (See ASHLAND on page 336)

CHICAGO
H-5D, L-28H
IAP, AD