

ST LOUIS

CREVE COEUR (1H0) 4 NW UTC-6(-5DT) N38°43.64' W90°30.51'

462 B TPA—See Remarks NOTAM FILE STL

RWY 16-34: H4500X75 (CONC) S-30 MIRL

RWY 16: REIL. PAPI(P4L)—GA 3.0° TCH 40'. Rgt tfc.

RWY 34: REIL. PAPI(P4L)—GA 3.0° TCH 43'.

RWY 07-25: 3079X220 (TURF)

RWY 25: Rgt tfc.

SERVICE: S3 FUEL 100LL, JET A LGT SS-SR REIL Rwy 16 and 34; MIRL Rwy 16-34 preset low intst; incr intst—CTAF. ACTVT REIL Rwy 16 and 34—CTAF.

AIRPORT REMARKS: Attended 1400Z±-dusk. Deer on and invof arpt. Heli ops on and invof arpt; wkend antique acft ops on and invof arpt. Hover taxi trng parl Rwy 07-25. Be alert to increased antique acft ops on and invof arpt on weekends. Rwy 16-34 12,500 lb max GWT or less; PPR more than 12,500 lb—amgr. Ultralight and TGL ops NA. Twy and apron strength—amgr. TPA—1112(650) and 1462(1000) for acft over 12,500 pounds. Rwy 07 marked with yellow cones. Rwy 25 marked with yellow cones. Rwy 16 markings faded. Rwy 34 markings faded.

AIRPORT MANAGER: 314-878-9575

COMMUNICATIONS: CTAF/UNICOM 122.8

Ⓜ **SAINT LOUIS APP/DEP CON** 126.5

CLEARANCE DELIVERY PHONE: For CD ctc St Louis Apch at 314-890-1017.

RADIO AIDS TO NAVIGATION: NOTAM FILE STL.

FORISTELL (L) (L) VORTACW 110.8 FTZ Chan 45 N38°41.66' W90°58.28' 080° 21.8 NM to fld. 819/5E.

TACAN AZIMUTH unusable:

265°-285° byd 35 NM blo 2,500'

ST LOUIS

L-27B, A

IAP

