LANAI (LNY)(PHNY) 3 SW UTC-10 N20°47.14′ W156°57.09′ B TPA—See Remarks Class I, ARFF Index A NOTAM FILE LNY

PUNN ISI NAIIAWAH P\_2G

RWY 03-21: H5001X150 (ASPH-GRVD) S-75, D-110, 2D-170, C5-517 PCR 317 F/B/X/T MIRL

IAP

RWY 03: PAPI(P4R)-GA 3.0° TCH 49'.

RWY 21: PAPI(P4L)—GA 3.76° TCH 45'. Antenna.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 03: TORA-5000 TODA-5000 ASDA-5000 LDA-5000 RWY 21: TORA-5000 TODA-5000 ASDA-5000 LDA-5000

SERVICE: FUEL JETA LGT ACTIVATE PAPI Rwy 03 and Rwy 21, MIRL Rwy 03-21—CTAF. Rwy 21 PAPI unusable byd 2 NM due to terrain.

AIRPORT REMARKS: Attended 1600-0400Z. Jet A fuel 5000 gal. POC (808) 286-7075. 24 hrs PPR for Division 1.1, 1.2, 1.3 explosives and 4 hrs PPR for hazardous material in/out of arpt ctc (808) 565-7941/7943. Arpt CLOSED to air carrier ops with more than 10 passenger seats 0530–1600Z except PPR, call (808) 565–7942. TPA--- small acft 2100 (792) large acft 2800 (1492). Possible severe updrafts/downdrafts from 2 mile final apch to Rwy 3 thld. Due to ramp limitations all acft parking limited to one hour except via PPR call (808) 565-7942, FAX (808) 565-7940 or (808) 872-3880. Jet parking SW side of ramp is conc. Fixed wing transient parking SW side of ramp is asph. NOTE: See Area

Notices—TRAFFIC ADVISORIES AT NON-TOWER ARPTS.

AIRPORT MANAGER: (808) 872-3830

WEATHER DATA SOURCES: AWOS-3P 118.375 (808) 565-6586.

COMMUNICATIONS: CTAF 122.9

LANAI RCO 122.5R, (serves OGG VORTAC 115.1T & LNY VORTAC 117.7T) (HONOLULU RADIO)

RHCF CENTER APP/DEP CON 119.3

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Honolulu Control Facility at 808-840-6262.

AIRSPACE: CLASS E svc continuous.

RADIO AIDS TO NAVIGATION: NOTAM FILE LNY.

(H) VORTAC 117.7 LNY Chan 124 N20°45.87′ W156°58.13′ 027° 1.6 NM to fld. 1252/11E.

TACAN unusable:

005°-063° byd 20 NM blo 15,000′

VOR unusable:

020°-060° byd 27 NM blo 5,000′

ILS/DME 111.1 I-LNY Chan 48 Rwy 03. Class IT. ILS unmonitored. Glideslope unusable for coupled apchs blo 1,505 'MSL.

## MAUI

HALEAKALA N20°42.32′ W156°15.90′ RCO 122.2 (HONOLULU RADIO) ------

**PANALIAN ISI ANDS** 

HAWAIIAN ISI ANDS P\_2G

P-2G

IAP

HANA (HNM)(PHHN) 3 NW UTC-10 N20°47.74′ W156°00.87′

78 B TPA—See Remarks NOTAM FILE HNM

RWY 08-26: H3606X100 (ASPH) S-34, D-48, 2D-80 MIRL

0.7% up W

RWY 08: PAPI(P2L)-GA 3.6° TCH 26'.

RWY 26: Rgt tfc.

SERVICE: LGT ACTIVATE MIRL (only high intensity avbl) Rwy 8-26-CTAF. Rwy 08 PAPI daylight ops only. Rwy 08 PAPI OTS indef.

AIRPORT REMARKS: Attended 1745-0230Z, Wild boars on and invof arpt. Parachute Idg area on east infield btn Twy B and C. Helicopter pilot training maneuvers will be conducted at the approach end of Rwy 26 only. Ultralights on and invof arpt. 24 hrs PPR for Division 1.1, 1.2, 1.3 explosives and 4 hrs PPR for other hazardous cargo in/out of arpt ctc (808) 248-4861 or (808) 872-3880. Rwy 08-26 35' trees along both sides of rwy 200' from centerline. Helicopter parking on grass infield areas between ramp and runway. TPA-Traffic pattern altitudes small acft 800(722) large acft 1500(1422). NOTE: See Area Notices—TRAFFIC ADVISORIES AT NON-TOWER AIRPORTS.

AIRPORT MANAGER: (808) 872-3808

WEATHER DATA SOURCES: AWOS-3PT 118.325 (808) 248-4864.

COMMUNICATIONS: CTAF 122.9

HANA RCO 122.3 (HONOLULU RADIO)

(R) HCF CENTER APP/DEP CON 118.45 278.3

CLEARANCE DELIVERY PHONE: For CD ctc Honolulu Control Facility at 808-840-6262.

RADIO AIDS TO NAVIGATION: NOTAM FILE OGG.

MAUI (H) VORTAC 115.1 OGG Chan 98 N20°54.39' W156°25.26' 095° 23.8 NM to fld. 24/11E.

000000000 . <sup>C</sup> C C C C C ପ ପ ପ ପ 3606 X 100