

MONTEREY RGNL (MRY)(KMRY) 3 SE UTC-8(-7DT) N36°35.22' W121°50.57'

SAN FRANCISCO

257 B TPA—1757(1500) LRA Class I, ARFF Index B NOTAM FILE MRY

H-3B, L-3B

RWY 10R-28L: H7175X150 (ASPH-GRVD) S-94, D-157, 2S-175, 2D-259 PCR 370 F/B/X/T HIRL 1.4% up E

IAP, AD

RWY 10R: MALS R. PAPI(P4L)—GA 3.0° TCH 47'. RVR-TR Thld dsplcd 175'.

RWY 28L: REIL. PAPI(P4R)—GA 3.5° TCH 45'. RVR-TR Thld dsplcd 175'. Rgt tfc.

RWY 10L-28R: H3503X60 (ASPH) S-12.5 PCR 370 F/B/X/T MIRL 1.7% up E

RWY 10L: REIL. PAPI(P2L)—GA 3.0° TCH 46'.

RWY 28R: REIL. PAPI(P2L)—GA 3.85° TCH 49'. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 10R: TORA-7175 TODA-7175 ASDA-7175 LDA-7000


RWY 28L: TORA-7175 TODA-7175 ASDA-7175 LDA-7000

ARRESTING GEAR/SYSTEM

RWY 10R: EMAS

RWY 28L: EMAS

SERVICE: S4 FUEL 100LL, JET A OX 2, 4 LGT When twr clsd, ACTIVATE MALS R Wwy 10R, REIL Wwy 28L, PAPI Wwy 10L, 10R, Wwy 28L and 28R, HIRL Wwy 10R-28L—CTAF. When twr clsd REIL 10L and Wwy 28R, MIRL Wwy 10L and Wwy 28R unavbl. Wwy 28L VGSi unusbl byd 2 deg L of rwy cntrln and wi .75 NM of rwy thr.



NOISE: Noise abatement procedures in effect 0700-1500Z±. Avoid flying Wwy 28L RNAV Y when possible to reduce noise impacts. Wwy 28L RNAV and RNP apchs are not to be used for practice apchs. Please avoid flights over residential areas, N and S. Ctc arpt ops 831-648-7000 option 2 or www.montereyairport.com for procedures. Rotary wing acft expect to follow fixed wing pattern to rwy ldg. On departure no turns blo 900' unless twr directed.

AIRPORT REMARKS: Attended continuously. Wwy 10L-28R not avbl for air carrier use. Fire station apron clsd to hel tfc. Wwy 10L-28R not avbl for sked acr opns with more than 9 psgr seats or unsked acr at least 31 psgr seats. Twr non-visibility area Twy A east holding bay. Acft with wingspan greater than 95' may not taxi past the terminal on Twy Alpha when an MD-80 or 757 is parked at terminal. Acft with wingspan greater than 65' prohibited on Twy Bravo between Twy Echo and Twy Delta. Facility constraints for commercial diversions. ADG III and larger with seating capacity more than 150 passengers are highly discouraged. CBP processing facilities unavailable. Overnight tiedown fee at FBO, ldg fee charged for acft over 6,000 lbs and helicopters. Overnight tiedown fee at FBO. Ctc FBO for rates and charges. Ltd transient parking PPR rqrld for large and turbine powered multi-engine acft, 831-648-7000 option 2. NOTE: See Special Notices—Arrival Alert.

AIRPORT MANAGER: 831-648-7000

WEATHER DATA SOURCES: ASOS (831) 642-0241

COMMUNICATIONS: CTAF 118.4 ATIS 119.25 831-375-7433 UNICOM 122.95

Ⓜ **NORCAL APP/DEP CON** 133.0 (001°-135° MRY) 127.15 (136°-360° MRY)

TOWER 118.4 (1400-0500Z±) **GND CON** 120.875 **CLNC DEL** 135.45

CLEARANCE DELIVERY PHONE: For CD or cnl IFR when ATCT clsd, ctc NorCal app con on 133.5; if una, ctc NorCal Apch at 916-361-3748.

AIRSPACE: CLASS C svc ctc **APP CON** svc 1400-0500Z±; other times CLASS E.

CONTINUED ON NEXT PAGE

CONTINUED ON NEXT PAGE

RADIO AIDS TO NAVIGATION: NOTAM FILE SNS.

SALINAS (VH) (H) VORTACW 117.3 SNS Chan 120 N36°39.83' W121°36.19' 231° 12.5 NM to fld. 81/17E.

VOR unusable:

010°-016° byd 22 NM blo 7,000'
 010°-016° byd 26 NM blo 8,000'
 016°-080° byd 22 NM blo 8,000'
 109°-119° byd 40 NM blo 6,000'
 109°-119° byd 58 NM
 135°-250° byd 40 NM
 150°-170° byd 8 NM blo 10,000'
 295°-302° byd 40 NM
 303°-313° byd 40 NM blo 18,000'
 314°-338° byd 40 NM
 339°-349° byd 40 NM blo 18,000'
 350°-108° byd 40 NM

TACAN AZIMUTH unusable:

010°-080° byd 22 NM blo 8,000'
 150°-200° blo 11,000'
 245°-255° byd 20 NM

Aerobatic acct wi an area defined as .5 NM rds of SNS 357016.4 (5.3 NM W CVH), blo 3000', avoidance advised SR-SS.

DME unusable:

010°-080° byd 22 NM blo 8,000'
 150°-200° blo 11,000'

ILS/DME 110.7 I-MRY Chan 44 Rwy 10R. Class IA. ILS/DME unmonitored when ATCT closed. LOC unusable within 0.5 NM from thld.

LOC/DME 110.7 I-MTB Chan 44 Rwy 28L. LOC/DME unmonitored when ATCT closed. LOC unusable abv 2,000' MSL, 2 DME inbound to thld. LOC/DME not avbl when ATCT clsd.

COMM/NAV/WEATHER REMARKS: ASR-11 antenna located Marina Muni (OAR), remoted to Monterey Rgnl (MRY). ASR-11 serves MRY and OAR.

MONTGOMERY-GIBBS EXEC (See SAN DIEGO on page 268)**MORRO BAY** N35°15.14' W120°45.57' NOTAM FILE HHR.

LOS ANGELES

(VL) (L) VORTACW 112.4 MQO Chan 71 083° 5.8 NM to San Luis Obispo Co Rgnl. 1463/16E.

H-4H, L-3D, 7A

VOR unusable:

092°-100° byd 40 NM
 193°-205° byd 40 NM
 290°-315° byd 7 NM blo 4,000'
 297°-315° byd 13 NM blo 7,000'
 315°-090° byd 7 NM blo 7,000'
 350°-082° byd 40 NM

MOUNT SHASTA MHS N41°19.00' W122°19.00' /3538

KLAMATH FALLS

ASOS 120.775 (530) 926-1613

H-3B, L-2I

MOUNTAIN VALLEY (See TEHACHAPI on page 293)