OHIO 329

```
YOUNGSTOWN/WARREN RGNL (YNG)(KYNG) P (AFRC) 10 N UTC-5(-4DT) N41°15.70′
```

W80°40.82

DETROIT H-10G, L-30H IAP. AD

1192 B ARFF Index—See Remarks NOTAM FILE YNG
RWY14-32: H9003X150 (ASPH-GRVD) PCN 82 F/C/W/T HIRL
RWY14: MALSR. PAPI(P4L)—GA 3.0° TCH 35′ RVR-R 0.9% up.
RWY32: MALSR. PAPI(P4L)—GA 3.0° TCH 35′ RVR-T Trees

**RWY 32**: MALSR. PAPI(P4L)—GA 3.0° TCH 35′. RVR-T Trees. 0.8% down. **RWY 05-23**: H5002X150 (ASPH-GRVD) S-138, D-175, 2S-175.

2D–280 PCN 42 F/C/W/T  $\,$  MIRL  $\,$  1.4% up NE RWY 05: REIL. PAPI(P4R)—GA 3.25° TCH 51  $\dot{}$  . Trees.

RWY 23: REIL. PAPI(P4R)-GA 3.0° TCH 24'.

RWY 143-323: H3501X60 (ASPH) 1.4% up SE

## RUNWAY DECLARED DISTANCE INFORMATION

 RWY 05: TORA-5002
 TODA-5002
 ASDA-5002
 LDA-5002

 RWY 14: TORA-9003
 TODA-9003
 ASDA-9003
 LDA-9003

 RWY 14: TORA-3500
 TODA-3500
 ASDA-3500
 LDA-3500


 RWY 23: TORA-5002
 TODA-5002
 ASDA-5002
 LDA-5002

 RWY 32: TORA-9003
 TODA-9003
 ASDA-9003
 LDA-9003

 RWY 32: TORA-3500
 TODA-3500
 ASDA-3500
 LDA-3500

 LDA-3500
 LDA-3500
 ASDA-3500
 LDA-3500

SERVICE: S4 FUEL 100LL, JET A 0X1, 2, 3, 4 LGT Rwy 23 PAPI unusable byd 8° left of rwy centerline. Rwy 32 PAPI unusable byd 8° right of centerline. MILITARY— FUEL J8+100(Mii) J8-PN rqr. (NC-100LL, A) FLUID LOX(Mii) 0IL 0-156



AIRPORT REMARKS: Attended continuously. Deer and bird haz. All military acft ctc Vader ops for bird watch condition. Rwy 143–323 used as a military assault strip. Class IV, ARFF Index A. Clsd to skedd acr ops gtr than 9 pax seats. 12 hrs PPR for unsked acr ops with more than 30 pax seats call arpt ops mgr 330–609–5007. ARFF Index D avbl 12 hrs PPR ctc 330–609–1369. Twy G east of Twy H and Twy F north of Rwy 05–23 are clsd. Twy T west of Rwy 05–23 closed indef. Commercial ramp closed to all general aviation traffic, commercial bdry area defined by red sfc painted marking. Terminal ramp and general aviation parking not visible from the northwest portion of Twy H. Twy J acft turn radius restriction exists for acft having nose gear to main gear distance greater than 64' and main gear width greater than 30'. Military ramp for military use only. Ldg fee for acft over 5,000 lbs gross weight.

MILITARY REMARKS: RSTD Mil Idg zone 143–323 and mil ramp for mil use only. No practice apch 0300–1300Z‡. Area W of trml and coml ramp clsd to general avn defined by red line on ramp. All mil acft opr rstd dur Bird Watch Cond MODERATE (tkof and Idg perms only when dep/arr rte avoid ident bird act, no Id IFR/VFR ftc pat act) and SEVERE (tkof and Idg proh wo OG/CC apvl). CAUTION Deer and bird haz, mil acft ctc Vader OPS for bird watch cond. Trees at end Rwy 32. Trml and general avn prk not vis fr NW portion of Twy H. Mil conducting NVG ops Mon–Fri dusk–0900Z‡. MISC FBO line svc avbl 1100–0400Z‡, OT fone C330–442–3374. AFRC PPR for ramp and mil LZ ctc BASOPS 1230–0400Z‡ Mon–Fri exc hols (DT 1130–0400Z) and dur unit trng Sat 1300–2200Z‡ and Sun 1200–2100Z‡. 48 hrs PN for ramp ctc afld mgmt DSN 346–1069/1181, C330–609–1069/1181. Afld mgmt and mil LZ 143/323 open 1230–0400Z‡ Mon–Thu and 1230–0001Z‡ Fri, exc hols, 1200–2100Z‡ Sat and Sun durg unit trng. AMOPS does not issue or stor COMSEC. Ltd COMSEC stor avbl at Comd Post, ctc DSN 346–1315, C330–609–1315 for prior coord. No tran alert svc. Inbd mil acft indicate in rmk DD Form 175 whether prk will be on civ or mil ramp. Tran acft rqr maint will be recovered by home base. Acft security not avbl for C5 RON exc emerg. Mil Idg zone 323 1.4 percent downslope. Mil Idg zone 143 1.4 percent upslope. Aircrews—US CSTMS Svc not immed avbl. All support for CSTMS must be pre–coord at least 72 hr in advance with Afld Mgmt.

AIRPORT MANAGER: 234-228-9696

WEATHER DATA SOURCES: ASOS (330) 856-9357

COMMUNICATIONS: ATIS 123.75 UNICOM 122.95

RCO 122.2 (CLEVELAND RADIO)

- ® YOUNGSTOWN APP/DEP CON 133.95 (1100-0500Z‡)
- ® CLEVELAND CENTER APP/DEP CON 120.775 (0500-1100Z‡) ctc Cleveland ARTCC at 440-774-0227.

TOWER 119.5 GND CON 121.9 CLNC DEL 118.25

CLEARANCE DELIVERY PHONE: For CD ctc Youngstown Apch at 330-856-4806, when Apch clsd ctc Cleveland ARTCC at 440-774-0232.

AIRSPACE: CLASS D.

TRSA svc ctc APP CON within 20 NM

RADIO AIDS TO NAVIGATION: NOTAM FILE YNG.

(L) TACAN Chan 27 YNG (109.0) N41°19.86′ W80°40.48′ 189° 4.2 NM to fld. 1158/5W.

**FETCH NDB (LOMW)** 338 YN N41°12.03´ W80°35.77´ 322° 5.3 NM to fld. 1029/8W. NDB unmonitored. NDB unusable:

Bvd 10 NM

ILS 110.1 I-MQK Rwy 14. Class IE. OM unmonitored.

ILS 110.1 I-YNG Rwy 32. Class IA. LOM FETCH NDB. LOM unmonitored. LOM unusable byd 10 NM.

ASR (1100-0500Z‡)