

LAKELAND

LAKELAND LINDER INTL (LAL)(KLAL) 4 SW UTC-5(-4DT) N27°59.26' W82°01.14'

MIAMI
H-8H, L-21D, 24F
IAP, AD

142 B ARFF Index—See Remarks NOTAM FILE LAL

RWY 10-28: H8500X150 (ASPH-GRVD) S-50, D-250, 2D-550,

2D/2D2-1120 PCR 460 F/A/X/T HIRL CL

RWY 10: ALSF2. TDZL. PAPI(P4R)—GA 3.0° TCH 71'. RVR-TMR

RWY 28: PAPI(P4L)—GA 3.0° TCH 71'. RVR-TMR Trees.

RWY 05-23: H5000X150 (ASPH-GRVD) S-94, D-150

PCR 320 F/A/X/T HIRL

RWY 05: PAPI(P4L)—GA 3.0° TCH 59'.

RWY 23: PAPI(P4L)—GA 3.0° TCH 46'. Trees.

RWY 08-26: 2208X60 (TURF)

RWY 08: Thld dspld 362'. Trees.

RWY 26: Thld dspld 556'. Hangar.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 05	10-28	2500

RUNWAY DECLARED DISTANCE INFORMATION

RWY 05: TORA-5000 TODA-5000 ASDA-5000 LDA-5000

RWY 08: TORA-1650 TODA-2010 ASDA-2205 LDA-1845

RWY 10: TORA-8500 TODA-8500 ASDA-8500 LDA-8500

RWY 23: TORA-5000 TODA-5000 ASDA-5000 LDA-5000

RWY 26: TORA-1845 TODA-2205 ASDA-2205 LDA-1650

RWY 28: TORA-8500 TODA-8500 ASDA-8500 LDA-8500

SERVICE: S4 FUEL 100LL, JET A QX 1, 2 LGT Twy D, D1, & E1 unlgtd.

AIRPORT REMARKS: Attended continuously. Bird act on and invof arpt. Rwy 08-26 mkd with pavers. Rwy 05-23 sked acr ops with more than 9 pax seats or unsked acr with at least 31 pax seats NA. Rwy 08-26 rstrd to Group 1 acft under 1500 lbs MTOW, VFR daytime only, no tgl; PPR—863-834-4911. Class I, ARFF Index B. Index C avbl upon req. Rwy 08-26 sked acr ops with more than 9 pax seats or unsked acr with at least 31 pax seats NA. PJE within 5 NM 18,000 blw SR-SS. USCBP user fee arpt; svc Thur-Mon, 1530-2400Z+. Fee chrgd outside of svc hours. Fee payable on site. User fee arpt.

AIRPORT MANAGER: 863-834-3298

WEATHER DATA SOURCES: AWOS-3PT (863) 834-2030 LAWRS.

COMMUNICATIONS: UNICOM 122.95 ATIS 118.025

RCO 122.1R 116.0T (SAINT PETERSBURG RADIO)

® TAMPA APP/DEP CON 120.65 119.9

TOWER 124.5 GND CON 121.4

AIRSPACE: CLASS D.

RADIO AIDS TO NAVIGATION: NOTAM FILE LAL.

(VH) (H) VORTAC 116.0 LAL Chan 107 N27°59.17' W82°00.83' at fld. 134/1E.

TACAN AZIMUTH unusable:

321°-339° blo 6,000'

VOR unusable:

020°-045° byd 40 NM

060°-073° byd 40 NM blo 2,500'

060°-073° byd 56 NM

070°-100° byd 35 NM blo 1,400'

074°-090° byd 40 NM blo 2,600'

074°-090° byd 51 NM

197°-207° byd 40 NM blo 2,000'

197°-207° byd 49 NM

317°-324° byd 40 NM

325°-335° byd 40 NM blo 2,000'

325°-335° byd 57 NM blo 3,000'

325°-335° byd 61 NM

ILS/DME 110.1 I-LAL Chan 38 Rwy 10. Class IIIE.

