FLORIDA 131

MACDILL AFB (MCF)(KMCF) AF (A) 4 S UTC-5(-4DT) N27°50.96′ W82°31.27′

4 B LRA NOTAM FILE MCF Not insp.

MIAMI H-8H, L-21D, 24F DIAP. AD

RWY 05-23: H11421X151 (ASPH-GRVD) PCN 71 R/B/W/T HIRL

RWY 05: ALSF1. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T RWY 23: ALSF1. PAPI(P4L)—GA 3.0° TCH 56'. RVR-T

ARRESTING GFAR/SYSTEM

RWY 05 HOOK BAK-12B(B) (1338 FT).

HOOK BAK-12B(B) (1397 FT) RWY 23

SERVICE: FUEL JET A, A++ 0X2 MILITARY—LGT HIRL Rwy 05–23 opr when twr opn. Rwy 05–23 PAPI set for hgt group 3. A–GEAR Rwy 05–23 N and S BAK–12B avbl Mon–Fri 1300–2030Z‡; 45 min PN to cnct cable, unavbl drg wkend and federal hol. JASU (A/M32A–86) (AM32–95) (M32A–60) FUEL A++. Air Card rqrd for avn fuel or U.S. cash; cash fuel PPR—fuels DSN 968–2074. FLUID LPOX LOX TRAN ALERT Opr 1100–0300Z‡. Lavatory svc only, PPR. Ltd tran prk for tactical acft; exp svc delay for tactical acft. Unable to svc acft with ordnance. Tran Alert is contract maint. Tran acft must land by 0230Z‡ exc VIP. All ftr type/trainer acft must land by 0200Z‡. No multiple IFR/VFR apch for tran acft after 0230Z‡. Tran Alert can support minimal tran acft for Icl or out and back tran fits with prior apvl. All series B–747 and A–380 must arrive with a tow bar.

MILITARY REMARKS: Attended continuously. Rwy 05-23 mkd 150 ft wide with 50 ft wt brg shoulders each side. First 1000 ft conc mid 9420 ft asph. RSTD Avoid ovft of the St. Petersburg land mass by at least 1.5 NM. PPR—Base Ops DSN 968-2929/2350, C813-828-2350/2929, for PPR nr, for svc and other rstd. PPR issued up to 7 days prior to arr. All acft dep MacDill AFB must have FLP on file in AMOPS prior to tkof. All acft must land by PPR approved time or call with deviations or PPR is invalid; exc for VIP. All DV acft and tnst acft ctc MacDill Cmd Post 311.0 or DSN 968-4361/4362 (C813-828-4361) 3 hr prior to arr and 30 min prior to arr with DV codes, customs info and Space-A pax info. All aircrew dep civ arpt or guard/reserve base call Comd Post 1 hr prior to takeoff with pax/cargo/eta info. PPR number good for req day only. S ramp (B ramp), electrical box 116' and fence 138' from twy cntrln. Acft opr rstd dur Bird Watch Cond Moderate (tkf or Idg permission only when departure and arr rte avoid identification bird act. No Icl IFR/VFR tfc pat act) and Severe (tkf and ldg prohibited without OG/CC apvI), ctc ATIS, Twr, Comd Post, or AMOPS for current Bird Watch Cond. All acft dep MacDill AFB, with exc to no DOD affilitated acft, must leave copy of FPL with Afld Mgmt. Cargo/hvy acft Indg on BAK-12 cables na. Helipad H1 (100' x 100' con) USA res avn support fac MacDill use only. Deployed unit cmplx apn (Delta/DUCC Ramp) clsd. CAUTION Bird haz; exp hvy bird act fm Nov 1-Feb 28 durg Phase II BASH period; 24 hr bird watch alert in effect. Numerous voids/sinkholes on afld; remain on twy cntrln. See FLIP AP/1 Supplementary Arpt Remarks for bird haz info. On inst apch to Rwy 23, use caution dur ovft of Peter O. Knight Arpt due to Igt acft tfc blw apch leg 4 NM NE. Commercial acft cross apch to MacDill AFB enroute to Tampa Intl Arpt at and abv 2100 ft. On inst apch to Rwy 05 use caution dur ovft of Albert Whitted Arpt due to Igt tfc blw apch leg 6 NM SW. Maint rwy and twy cntrline when exiting rwy. Acft making 180° turns on rwy use hammerheads last 1000 ft at each end. Use ctn durg taxiing ops at night on spots A1-A4 due to removed apn Igtg. Taxilane H, fence 107' from twy cntrln, all acft larger than KC-135 need wing walkers and tran alert follow me vehicle. S ramp (Bravo ramp) electrical box 116' from twy cntrln and fence 138' from twy cntrln, all acft larger than KC-135 need wing walkers and tran alert follow me vehicle. DV-4 spot is for C12, C21 acft tight turn radius. Unctl VFR tfc in vcnty of KMCF blw 1200'. Nstd ovrn mrk MacDill AFB on Rwy 05-23 ends. Nstd mrks north/south ramps, wing-tip obst lines for trng. NSTD acft turning RAD on tran spots 16-25, follow tran alert vehicle. Birdbath only used for P-3, C-130, E-3A, KC-135 & B-737 acft no ftr or copter unless apvd by afm, IFC PAT Rectangular 1100 ft; ovhd 1600 ft. Drg VFR cond tkof and TGL mntn 1100 ft til DER. Heli 600'. CSTMS/AG/IMG CSTMS/AG/IMG See FLIP AP/1. MISC MacDill crash fire response (CFR) is an acft rescue and firefighting (ARFF) CAT 4 with 7,800 gal capability. Steady ARFF cond for MacDill AFB is optimum level of svc (OLS) for CAT 1-3, and Reduced Level of Svc (RLS) for CAT 4-6. ATC/Wx will not incld/relay wind correction into fcst/phraseology, therefore, aircrews will incorporate a +/-. Wx flt ops 24 hrs. Excld hol or dur severe wx. Wx flt DSN 968-4405/2854/2035, C813-828-4405/2854/2035. During afld closures ctc 26 OWS, DSN 331-2651, C318-529-2651. When possible, provide 2 hr adv ntc for all rqrd briefings. When NVD ops are in efct ctc twr 10 min prior to arr or dep for afld lgt adi-info DSN 968-2120/4822. All acft reg to park on army app must ctc ASF Macdill C813-828-3180/3183 up to 7 days prior to arr/mnm notice is 24 hr prior to arr, Class D airspace reverts back to Class G when twr is clsd. Txv and Ramp Restrictions — Acft with wingspan greater than 170' rgr wing walkers at the int of the Bravo Apron and Txy Kilo due to light pole obstn. Light pole is located 129' north of Txy Kilo cntrln. Wide body acft with wingspans greater than 132.7' will not be allowed to txy on txy Inaes located on the Alpha Apn without wing-walkers. NOTE: See Special Notices-Airspace delegated to MACDILL AFB.

COMMUNICATIONS: SFA ATIS 133.825 270.1 PTD 372.2 (Unsvc. Ctc AMOPS C813-828-0002)

R TAMPA APP CON 124.95 354.0

TOWER 120.175 294.7 GND CON 118.575 275.8

® TAMPA DEP CON 119.9 290.3 (Rwy 05) 119.65 353.575 (Rwy 23)

6 AMW COMD POST (LIGHTNING OPS) 311.0 323.8

PMSV METRO 225.05 (PMSV O/S UFN. PIs ctc 6 OSS/OSW WX at (813)–828–4405 for WX info.)

AG See Global HF Sys listing in Flight Information Handbook.

CONTINUED ON NEXT PAGE

132 FLORIDA

CONTINUED FROM PRECEDING PAGE

```
AIRSPACE: CLASS D svc continuous.
        RADIO AIDS TO NAVIGATION: NOTAM FILE MCF.
          (L) TACAN Chan 47 MCF (111.0) N27°51.67′ W82°30.81′ at fld. 12/6W.
            mp 0900-2300Z‡ Fri
          TACAN AZIMUTH unusable:
            230°-240° byd 30.0 NM
            240°-245° byd 30 NM
            246°-341° byd 35 NM
            342°-345°
            346°-011° byd 35 NM
          DME unusable:
            230°-240° byd 30 NM
            241°-284° byd 35 NM
            296°-345° bvd 35 NM
            342°-345° byd 32 NM
            346°-011° byd 35 NM
          ILS 109.5 I-MCF Rwy 05. Class IC. ILS - 05: Rwy 05 course line is offset 2.9° to SE, rwy hdg is 046 deg. Rwy
            23 course line is offset 2.7° to NE, rwy hdg is 226 deg. Mp 1200-1500Z‡ Tue and Thurs.
          ILS 111.7 I-GBZ Rwy 23. Class IB. Rwy 23 course line is offset 2.7° to NE, rwy hdg is 226 deg. MP
            1200-1500Z‡ Tue-Wed.
        COMM/NAV/WEATHER REMARKS: MacDill surveillance radar provided by Tampa. Tsnt aircrews may ctc 9 OWS for WX
          BRIEF-DSN 965-0939.
               ٠
                     .
                           ٠
        HELIPAD H1: H100X100 (CONC)
     MANATEE (See PALMETTO on page 155)
MARATHON
     THE FLORIDA KEYS MARATHON INTL (MTH)(KMTH) 3 E UTC-5(-4DT) N24°43.57′ W81°03.08′
                                                                                                               MIAMI
                                                                                                           H-8I. L-23C
            B ARFF Index—See Remarks
                                         NOTAM FILE MTH
                                                                                                              IAP AD
        RWY 07-25: H5008X100 (ASPH-GRVD) S-62, D-100, 2D-182 PCR 200 F/A/X/T MIRL
          RWY 07: REIL. PAPI(P4L)-GA 3.0° TCH 24'. Tree.
          RWY 25: PAPI(P4L)-GA 3.0° TCH 24'. Tree.
        RUNWAY DECLARED DISTANCE INFORMATION
          RWY 07: TORA-5008 TODA-5008 ASDA-5008 LDA-5008
          RWY 25: TORA-5008 TODA-5008 ASDA-5008 LDA-5008
        SERVICE: S2 FUEL 100LL, JET A1+ 0X1, 2, 3, 4 LGT ACTIVATE REIL Rwy 07; PAPI Rwy 07 and Rwy 25; MIRL Rwy
          07-25-CTAF.
        NOISE: Noise sens area; use NBAA noise abatement proc; Icl ordinance rgr eng runup in dsgnd area on coml or FBO ramp fm
          0400-1200Z‡ and fines.
        AIRPORT REMARKS: Attended 1300-2300Z‡. Birds on and invof arpt. Aft hr Jet-A fuel-305-481-7615. Self svc fuel H24.
          Class I, ARFF Index A. 48 hr PPR for unsked Part 121 ops with gtr than 30 pax seats. Twy A restrictions may apply to
          acft with a wingspan of 79 ft or greater when acft are ldg or taking off on Rwy 07-25. Arpt ops notification will be tmtd
          on CTAF. USCBP user fee fac open Thur-Mon 1400-2230Z‡. Clsd to arrs Tues and Wed except on req and apvl by USCBP
          at 305-289-2029. Flight Notification Service (ADCUS) avbl.
        AIRPORT MANAGER: 305-289-6302
        WEATHER DATA SOURCES: ASOS 135.525 (305) 743-8373.
        COMMUNICATIONS: CTAF/UNICOM 122.975
          MARATHON RCO 122.6 (MIAMI RADIO)
       ® MIAMI CENTER APP/DEP CON 133.5
        CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Miami ARTCC at 305-716-1731.
        RADIO AIDS TO NAVIGATION: NOTAM FILE EYW.
          KEY WEST (VH) (H) VORTAC 113.5 EYW Chan 82 N24°35.15′ W81°48.03′ 077° 41.8 NM to fld. 10/1E.
          VOR unusable-
            063°-066° byd 40 NM
            118°-124° byd 40 NM
            125°-135°
            136°-139° byd 40 NM
            140°-220° byd 30 NM
            221°-239° byd 40 NM
            310°-315° byd 40 NM
          TACAN AZIMUTH unusable:
            125°-135°
            140°-220° byd 30 NM
          DME unusable:
            140°-220° bvd 30 NM
```

COMM/NAV/WEATHER REMARKS: Arpt opr notification will be transmitted on CTAF 122.975.