66 ALABAMA

MAXWELL AFB (MXF)(KMXF) AF (AFRC)

```
H-6K, 9A, 12F, L-18I
         B TPA—See Remarks NOTAM FILE MXF Not insp.
                                                                                                             DIAP. AD
  RWY 15-33: H8008X150 (ASPH) PCN 66 R/B/W/T HIRL
     RWY 15: ALSE1, PAPI(P4L)-GA 3.0° TCH 46'.
    RWY 33: PAPI(P4L)-GA 3.0° TCH 50'.
  RWY 009-189: H3015X60 (ASPH) PCN 56 R/R/W/T
  SERVICE: MILITARY—LGT Rwy 15-33 70' gated thild lgt. Rwy 15-SSALR lgt sys avbl during VMC cond. Rwy 15 PAPI lateral
    coverage limitation set at 8 deg left and 12 deg right. Rwy 15 PAPI unusable byd 8 degs left and 12 degs right of
    centerline, JASU 4(A/M32A-86D) 2(AM32-95) FUEL A++ TRAN ALERT AIREVAC and DV acft will be given priority svcg.
  MILITARY REMARKS: Opr wkdays 1400-0400Z‡, wkends 1600-2400Z‡, clsd Federal hol. Seasonal hrs 1 Apr to 30 Sep
     1400-0600Z‡. 0400-0600Z‡ avbl to only 908th FTW acft. RSTD Dur Bird Watch Cond Code Moderate and Severe,
    aircrews should refer to AP/1 for BASH hazard conditions and restrictions; aircrews can obtain current Bird Watch Cond
    fr ATIS/PTD/twr. All aircraft with wingspan greater than C-130 (132 ´ 7") are restricted from taxiing to and from Delta and
     Echo Taxiways when C-130's are parked on the west ramp parking apron. All hvy acft will use Twy C to enter/exit to and
    fr NE. C-5, C-17, KC-10 and B747 are prohibited from 180° turns first 200′ Rwy 33. Ldg zone use authorized for C-130
    or smaller acft with paved ldg zone trng requirements, reference AP/1 for procedure/rstd. Ldg zone ldg rqr PPR. Ctc Afld
     Mgmt Ops DSN 493-6961/62 or C334-953-6961/62. Acft transporting DV to KMXF or Gunter Annex ctc PTD 30 min
     prior Idg. Overnight store of classified material will be provided by Maxwell Comd Post DSN 493-4747 or
     334-953-7474. CAUTION BASH Phase II bird activity June-Nov. Practice missed apch in VFR cond maintain rwy hdg blo
     1200' until over dep EOR then immediate rgt std rate turn to hdg 300° to avoid Dannelly Fld. Possible hydroplaning dur
     periods of rain on Rwy 15-33 and ldg zone 009-189. Ldg zone 009-189 is paved. Ldg zone 189 overrun extends onto
     Rwy 15-33. Aircrews use caution due to loss of wind speed blw 50' AGL when winds between 280-310 ldg Rwy 15.
     Unigtd turnaround on east side of dep end Rwy 33, AER 15 rstd to daylight VMC except for approval night vision ops.
    AER 33 does not have wx sensors. Data from Rwy 15 end sensors is considered representative for non-precision apch
     ldgs on Rwy 33 end. Potential for CAP-USAF acft departures dur clsd aerodrome hrs 0401-1359Z‡ wkd; 0001-1559Z‡
    wkend. TFC PAT TPA—Rectangular 1029' AGL, overhead 1529' AGL. Wind direction indicators, optical lgts are ctld by
    twr dur ngt opr hrs, reduced visibility, and IFR cond only. MISC Augmented wx obsn visibility rstd to 1/4-1 NM all quad
    exc northwest due numerous obst. Twr will conduct cooperative wx watch and supplement obsn as rqr. 1st 2207 ' Rwy
     15 is conc and grooved, next 3894' is asph, next 400' is conc overlay and grooved, remaining 1507' is asph, reverse
    order for Rwy 33. Landing zone 189, 1480 is conc and grooved. Rwy 15-33 will accept acft heavier than published wt
    bearing capacity, ctc Afld Mgmt OPS for wt bearing waiver. AFRC Opr wkdays 1315-2200Z‡, and unit trng assembly
    wkend, DSN 493-2717.
  AIRPORT MANAGER: 334-953-7406
  COMMUNICATIONS: ATIS 134.7 269.9 (1400-0400Z‡ wkdays, 1600-2400Z‡ wkends, clsd federal hol) PTD 139.3 372.2
 ® MONTGOMERY APP/DEP CON 121.2 269.05 (N) 124.0 363.025 (S) (1200-0500Z‡)
 R ATLANTA CENTER APP/DEP CON 120.55 270.25 (0500-1200Z‡)
     TOWER 118.15 253.5 (1400-0400Z‡ wkdays, 1600-2400Z‡ wkends, clsd federal hol)
    GND CON 127.15 289.4
    MAXWELL COMBINED COMD POST monitor 118.15 after nml duty hrs (Call BAMA-WOLF OPS).
    PMSV 342.3 (Full svc avbl 1400-0400Z‡ wkd, 1600-2400Z‡ wkend, clsd Federal hol. Aerodrome TAF completed by
    26th OWS; For updtd fcst ctc MXF Wx DSN 953-2071, C334-953-2071. ASOS in use, augmented when necessary dur
     afld opr hr.)
  CLEARANCE DELIVERY PHONE: When ATCT clsd, for CD ctc Atlanta ARTCC at 770-210-7692.
  AIRSPACE: CLASS D svc 1400-0400Z‡ Mon-Fri, 1600-0000Z‡ Sat-Sun, clsd fed hol; other times CLASS E.
  RADIO AIDS TO NAVIGATION: NOTAM FILE MXF.
    (L) TACAN Chan 97 MXF (115.0) N32°22.76′ W86°22.10′ at fld. 157/2W. TACAN unmonitored when ctl twr
       clsd
     TACAN AZIMUTH unusable:
       211°–229° byd 15 NM
       230°-245°
       246°-279° byd 15 NM
       280°-210° byd 25 NM blo 3,000°
       No NOTAM MP: 2000-1000Z‡ wkday; 2200-0600Z‡ wkend Z‡
    ILS 109.3 I-MXF Rwy 15. Unmonitored when ctl twr clsd. No NOTAM MP: localizer 1500-1800Z‡ Mon. Glideslope
       mp: 1500-1800Z‡ Tue.
                                                                                                             ATI ANTA
MCDEN N33°30.69′ W86°50.74′ NOTAM FILE BHM.
                                                                                                               L-18H
  NDB (HW/LOM) 224 BH 059° 5.6 NM to Birmingham-Shuttlesworth Intl. 569/3W.
```

2 NW UTC-6(-5DT)

N32°22.98′ W86°21.95′

ΔΤΙ ΔΝΤΔ

MERKEL FLD SYLACAUGA MUNI (See SYLACAUGA on page 78)