

**ELKO RGNL** (EKO)(KEKO) 1 W UTC-8(-7DT) N40°49.50' W115°47.48'

5140 B Class I, ARFF Index A NOTAM FILE EKO

**RWY 06-24:** H7454X150 (ASPH-GRVD) S-78, D-105, 2S-133, 2D-170

PCR 340 F/B/X/T MIRL 0.3% up NE

**RWY 06:** PAPI(P4L)—GA 3.0° TCH 44'. Road. Rgt tfc.

**RWY 24:** MALSR. PAPI(P4L)—GA 3.25° TCH 51'. Thld dspcd 1036'. Pole.

**RWY 12-30:** H3015X60 (ASPH) S-12 PCR 50 F/C/X/T 2.0% up NW

**RWY 12:** Thld dspcd 906'. Pole. Rgt tfc.

**RWY 30:** Thld dspcd 143'. Pole.

#### RUNWAY DECLARED DISTANCE INFORMATION

**RWY 06:** TORA-7217 TODA-7217 ASDA-7217 LDA-7217

**RWY 12:** TORA-3015 TODA-3015 ASDA-3015 LDA-2109

**RWY 24:** TORA-7454 TODA-7454 ASDA-7454 LDA-6418

**RWY 30:** TORA-3015 TODA-3015 ASDA-3015 LDA-2872

**SERVICE:** S4 FUEL 100LL, JET A OX 1, 2 LGT Actvt MALSR Rwy 24; MIRL Rwy 06-24—CTAF. PAPI Rwy 06 and 24 on consly. PAPI Rwy 24 does not provide obstruction clearance byd 6.5 NM from thld.

**AIRPORT REMARKS:** Attended 1300-0500Z. Incd bird act invof arpt Mar-Sep. Sfc conds not mnt dly 0500-1400Z. Fuel 100LL, A avbl 24/7. Tkt only on Rwy 12. Land only on Rwy 30. No touch and go landing Rwy 12-30. Rwy 24 designated calm wind rwy. Rwy 12-30 not avbl for scheduled acf ops with more than 9 psgr seats or unscheduled acf ops with at least 31 psgr seats. Steep slope/gradient. PPR for all acft operations over 100,000 pounds call 775-777-7190. Cold temperature airport. Altitude correction required at or below -25C.

**AIRPORT MANAGER:** 775-777-7194

**WEATHER DATA SOURCES:** ASOS 119.275 (775) 778-9639.

**COMMUNICATIONS:** CTAF/UNICOM 123.0

RCO 122.6 (RENO RADIO)

® **SALT LAKE CENTER APP/DEP CON** 132.25

**CLEARANCE DELIVERY PHONE:** For CD if una to ctc on FSS freq, ctc Salt Lake ARTCC at 801-320-2568.

**RADIO AIDS TO NAVIGATION:** NOTAM FILE EKO.

**BULLION (VL) (DH) VORW/DME** 115.85 BQU Chan 105(Y) N40°45.58' W115°45.68' 324° 4.1 NM to fld. 6466/17E.

VOR unusable:

042°-060° byd 40 NM

068°-115° byd 40 NM

088°-110° byd 32 NM

116°-126° byd 40 NM blo 26,000'

127°-135° byd 40 NM

144°-154° byd 40 NM

187°-225° byd 40 NM

287°-295° byd 40 NM

325°-332° byd 40 NM

DME unusable:

079°-100° byd 32 NM

088°-110° byd 20 NM

101°-130° byd 20 NM

111°-130° byd 32 NM

**LDA/DME** 108.5 I-EKO Chan 22 Rwy 24. LDA offset angle 5° 58 min. DME unusable byd 13 NM blw 9,000'.

