

NEWARK LIBERTY INTL (EWR)(KEWR) 3 S UTC-5(-4DT) N40°41.55' W74°10.12'

NEW YORK

18 B LRA Class I, ARFF Index E NOTAM FILE EWR

COPTER

RWY 04L-22R: H11000X150 (ASPH-CONC-GRVD) D-210, 2D-520, 2D/2D2-1000

H-101, 12J, L-33A, 34H

PCR 960 F/C/X/T HIRL CL

IAP, AD

RWY 04L: MALSR. TDZL. PAPI(P4L)—GA 3.1° TCH 77'. RVR-TMR Thld dsplcd 2541'. Tree.

RWY 22R: MALSR. TDZL. REIL. PAPI(P4L)—GA 3.1° TCH 66'. RVR-TMR Thld dsplcd 1441'. Pole.

RWY 04R-22L: H9999X150 (ASPH-GRVD) D-210, 2D-520, 2D/2D2-1000 PCR 1020 F/C/X/T HIRL CL

RWY 04R: ALSF2. TDZL. PAPI(P4L)—GA 2.95° TCH 71'. RVR-TMR Thld dsplcd 1190'. Pole.

RWY 22L: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 60'. RVR-TMR Thld dsplcd 1794'. Antenna.

RWY 11-29: H6725X150 (ASPH-GRVD) D-210, 2D-520, 2D/2D2-1000 PCR 950 F/C/X/T HIRL CL

RWY 11: TDZL. REIL. PAPI(P4R)—GA 3.0° TCH 60'. RVR-TMR Bldg.

RWY 29: TDZL. REIL. PAPI(P4R)—GA 3.0° TCH 60'. Thld dsplcd 224'. Sign.

LAND AND HOLD—SHORT OPERATIONS

LDG RWY	HOLD—SHORT POINT	AVBL LDG DIST
RWY 04L	11-29	7750
RWY 04R	11-29	8100
RWY 11	04R-22L	5700

RUNWAY DECLARED DISTANCE INFORMATION

RWY 04L: TORA-11000 TODA-11000 ASDA-11000 LDA-8459
RWY 04R: TORA-9999 TODA-9999 ASDA-9999 LDA-8809
RWY 11: TORA-6725 TODA-6725 ASDA-6725 LDA-6725
RWY 22L: TORA-9999 TODA-9999 ASDA-9999 LDA-8205
RWY 22R: TORA-11000 TODA-11000 ASDA-11000 LDA-9559
RWY 29: TORA-6725 TODA-6725 ASDA-6725 LDA-6501

ARRESTING GEAR/SYSTEM

RWY 11: EMAS

RWY 29: EMAS

SERVICE: S4 FUEL 100LL, JET A OX3 LGT Rwy status lgts in opr. Rwy 29 PAPI unusbl 4° left of cntrl.

NOISE: Noise restrictions call 212-435-3784 during normal business hrs.

AIRPORT REMARKS: Special Air Traffic Rules—Part 93. Attended continuously. Flocks of birds on and in/ovf airport. Para-sail and banner towing ops 1000' and blo in upper and lower New York bays including Rockaway Inlet indef. High volume of low level helicopter t/c arriving and departing Helo Kearny Heliport (65NJ) located 3.5 miles northeast of the arpt. Expect to leave and re-enter the Class B Airspace during moderate to heavy arrival periods. Rwy 04L-22R, south 1779' conc, north 1228' conc, center 7993' asph. Rwy 04R and Rwy 04L departures use upper antenna for ATC communications. When Rwy 04R/L in use, acft prkg at Trml A can exp to enter ramp via Twy A8, unless adzd by ATC. When Rwy 022L/R in use, acft prkg at Trml A can exp to enter ramp via Twy A10 or A12, unless adzd by ATC. Twy Z between Twy Z2 and Twy Z4 clsd to acft with wingspans in excess of 171'. ADG IV acft rstr from passing Twy Z3 on Twy Z. Twy Z east of Twy U acft speed restriction of 17 kts/20 mph max for all acft with wingspans in excess of 171'. All twys surrounding "Ballpark" parking area (Twy Y btn Twy S and Twy U, Twy S btn Twy Y and Twy K, Twy K btn Twy S and Twy B, Twy B btn Twy K and Twy U and Twy U btn Twy B and Twy Y) acft speed restriction of 17 kts/20 mph for all acft with wingspans in excess of 171'. Twy EE btn Rwy 04R-22L and Rwy 11-29 clsd to acft with wingspans in excess of 171'. Twy Y btn RM and Twy U, speed restriction of 17 kts/20 mph. Twy A btn Twy AA and ramp clsd to acft with wingspans in excess of 171'. Twy Z5 clsd to acft with wingspans in excess of 118'. Twy A11 W of Twy A acft spd rstr of 17 kts/20 mph max for all acft with wingspans in excess of 171'. Acft with wingspans in excess of 118' prohibited from turning S on Twy R from Twy B1. GA/intrnt ldg fees payable by major credit cards only. ASDE-X in use. Operate transponders with altitude reporting mode and ADS-B (if equipped) enabled on all airport surfaces. Ldg fee. Flight Notification Service (ADCUS) avbl.

AIRPORT MANAGER: 973-961-6161

WEATHER DATA SOURCES: ASOS (862) 381-4743 LLWAS. TDWR.

COMMUNICATIONS: D-ATIS ARR 115.7 D-ATIS SOUTH ARR/DEP 134.825 (973) 824-4417. UNICOM 122.95

Ⓡ NEWARK APP/DEP CON 128.55 (090°-240°) 132.8 (241°-269°) 127.6 (270°-330°) 132.7 (331°-089°)

Ⓡ NEWARK APP/DEP CON 119.2

TOWER 118.3 134.05 **GND CON** 121.8 126.15 **CLNC DEL** 118.85

PRE TAXI CLNC 118.85 **RAMP CTL** 132.45

CPDLC DCL (LOGON KUSA)

PDC

AIRSPACE: CLASS B See VFR Terminal Area Chart.

CONTINUED ON NEXT PAGE

