

WEST PALM BEACH**NORTH PALM BEACH CO GENERAL AVIATION** (F45) 12 NW UTC-5(-4DT) N26°50.76' W80°13.34'**MIAMI**

22 B NOTAM FILE MIA

L-23C**RWY 09R-27L:** H4300X100 (ASPH) S-12.5 PCN 11 F/A/Y/T MIRL**IAP, AD****RWY 09R:** REIL. PAPI(P2L)—GA 3.0° TCH 40'. Rgt tfc.**RWY 27L:** REIL. PAPI(P2L)—GA 3.0° TCH 40'. Tree.**RWY 14-32:** H4300X75 (ASPH) S-30 PCN 10 F/A/Y/T MIRL**RWY 14:** REIL. PAPI(P2L)—GA 3.0° TCH 40'. Trees. Rgt tfc.**RWY 32:** REIL. PAPI(P2L)—GA 3.0° TCH 40'. Trees.**RWY 09L-27R:** 3679X75 (TURF)**RWY 09L:** Tree.**RWY 27R:** Tree. Rgt tfc.**SERVICE:** S4 FUEL 100LL, JET A LGT Dusk-0200Z†; aft 0200Z†, ACTVT REIL Rwy 09R, 14, 27L and 32; MIRL Rwy 09R-27L and 14-32—CTAF. Rwy 14 thr mkr lctd 4' byd rwy end.**NOISE:** Noise abatement proc; Rwy 14-32 preferred ngt rwy; H24 noise abatement mntg—(561) 626-7631.**AIRPORT REMARKS:** Attended continuously. Bird act invof arpt. Extsv flt trng mult rwys. Arpt sfc cond not rptd for all rwys. FBO svc fee may apply. Practice apch Rwy 09R-27L mnt CTAF and yield to tfc pat. Rwy 09R TDZ mrks not std. Twy G1 clsd. Rwy 14-32 acft over 30,000 lbs NA. Rwy 09R-27L acft over 12,500 lbs GWT NA. Rwy 09L-27R thlds mkd with PVC pipe ev 200'. Rwy 14 thr mkr lctd 4' byd rwy end. 24 hr PPR reqstd for all acft equipped with weather modification eqpt or acft cpbl of weather modification and/or geoengineering by ctc the dept of arpt communications cntr at (561) 471-7420.**AIRPORT MANAGER:** 561-471-7420**WEATHER DATA SOURCES:** AWOS-3 119.975 (561) 630-6932.**COMMUNICATIONS:** CTAF/UNICOM 123.075**® PALM BEACH APP/DEP CON** 128.3**CLNC DEL** 120.825**CLEARANCE DELIVERY PHONE:** For CD ctc Palm Beach Apch at 561-684-9047.**RADIO AIDS TO NAVIGATION:** NOTAM FILE PBI.**PALM BEACH (VH) (H) VORTAC** 115.7 PBI Chan 104 N26°40.80' W80°05.19' 327° 12.3 NM to fld. 16/3W.

VOR unusable:

005°-015° byd 40 NM blo 5,000'

005°-015° byd 63 NM

016°-044° byd 40 NM

052°-062° byd 100 NM

052°-062° byd 40 NM blo 6,000'

052°-062° byd 81 NM blo 8,000'

185°-195° byd 13 NM

209°-219° byd 40 NM

257°-267° byd 40 NM

305°-324° byd 40 NM

332°-348° byd 40 NM

349°-353° byd 40 NM

354°-004° byd 40 NM blo 3,000'

354°-004° byd 53 NM

TACAN AZIMUTH unusable:

286°-296° byd 28 NM

ILS/DME 110.75 I-GHO Chan 44(Y) Rwy 09R. Unmonitored 0830-1600Z†.**COMM/NAV/WEATHER REMARKS:** 24-hr PPR reqstd for all acft equipped with weather modification eqpt or acft cpbl of weather modification and/or geoengineering by ctc The Dept of Aprt Communications Cntr at (561) 471-7420.