

MCCHORD FLD (JOINT BASE LEWIS—MCCHORD) (TCM)(KTCM) AF 3 S UTC-8(-7DT) N47°08.26' W122°28.59' SEATTLE
H-1B, L-1D
DIAP, AD

322 B TPA—See Remarks AOE NOTAM FILE TCM Not insp.
RWY 16-34: H10108X150 (ASPH-CONC-GRVD) PCN 60 F/A/W/T HIRL CL
RWY 16: ALSF1. PAPI(P4L)—GA 3.0° TCH 68'. RVR-T 0.4% up.
RWY 34: ALSF2. TDZL. PAPI(P4L)—GA 3.0° TCH 59'. RVR-T Rgt tfc.
RWY 16Z-34Z: H3000X60 (ASPH)

ARRESTING GEAR/SYSTEM
RWY 16 HOOK BAK-12B(B) (2450 FT). HOOK BAK-12B(B) (1668 FT). **RWY 34**

SERVICE: S4 **OX** 1, 2 **LGT** Visual TCH set for hgt Gp 3 acft only. Rwy 16-34 cntr 72' thld lgt removed. AMP-1/AMP-3 overt/covert assault strip lgt inst mid 5000' Rwy 16-34. **MILITARY— JASU** (MD-3M) 1(MD-3) 1(MA-1A) (AM32A-60) 1(MC-11) **FUEL** A+ + **FLUID** SP PRESAIR De-ice-Exp 3 hr delay. LHOX LOX OIL 0-128-133-148-156 SOAP - Results rqr 24 hr, 1530-0030Z± wkd exc hol, results not avbl OT. Tran acft req SOAP will arr with historical eng SOAP data for trend analysis. **TRAN ALERT** Opr H24. Delays can be exp. Prk ltd. All tran acft rqr tran alert follow me assistance.

MILITARY REMARKS: All twy edge lgt and Rwy 16-34 edge, cntrln, TDZ lgt equipped with nstd LED fixtures may not be compatible with all NVDs or enhanced flight vision systems. **RSTD** All acft inc sked AMC msn rqr PPR 24 hr prior to arr. PPR's effective +/- 1 hr. Tran acft park extremely ltd. Msn planners must ctc AMOPS when using McChord as divert base. AMOPS DSN 382-5611, C253-982-5611. Acft RON more than 3 days and/or rqr other than normal trans svc must ctc 62 AW/XP, 253-982-5890. All inbd acft must ctc Comd Post (Rainier Ops) no later than 30 min prior to ldg. AMC acft opr rstd dur Bird Watch Cond Moderate (tkf and ldg permission only when departing/arr rte avoid identified bird act, no lcl IFR/VFR tfc pat act) and Severe (tkf and ldg prohibited without OG/CC aplv), ctc PTD/ATIS/Command Post for current Bird Watch Cond. Tran aircrews conducting lcl area low-level training msn must receive lcl procedure/rstd briefing from 62 OSS/OSK at DSN 382-3615, C253-982-3615. **CAUTION** When performing pre-tkof end runup, align acft so that debris is not blown toward ADTAC alert hgr or adj acft prk ramp. Dur VFR cond, acft making lo apch, nml tkof, touch and go ldg, or missed apch remain at or blw 1800 ft til dep end of the rwy. 1,000 ft Rwy 16-34 is concrete; rwy is grooved. Rwy marked with white non-reflective 90 ft x 3500 ft VFR day time assault ldg zone. **CSTMS/AG/IMG** Unsked acft arr btn 0900-1400Z± may experience delays for CSTMS/AG/IMG inspections. **TFC PAT** Before ldg maintain tfc pat alt commensurate with safety as long as practicable. TPA—Rectangular 1800' (1478) overhead 2300' (1978). **MISC** Aircrews notify PTD anytime they plan to ldg in lcl IFR pat on separate clnc prior to or departure on filed flt plan. Base OPS DSN 382-5611, C253-982-5611. Rwy cond codes (RWYCC) unavbl.

AIRPORT MANAGER: 253-982-5611
WEATHER DATA SOURCES: ASOS (253) 982-3434
COMMUNICATIONS: D-ATIS 135.825 270.1 PTD 372.2
 Ⓡ **SEATTLE APP/DEP CON** 126.5 377.15
TOWER 124.8 259.3 **GND CON** 118.175 279.65
COMD POST 349.4 134.1
PMSV METRO 342.3 Wx svc avbl H24 exc dur afd/twr closure. DSN 382-3434/2112, C253-982-3434/2112. All obs provided by AN/FMQ-19 automated observing sys; augmented by human obsn when nec. Full svc PMSV avbl via phone patch with comd post. Tran aircrew ctc 25 OWS dur afd closure to request wx briefing DSN 228-6598, or C520-228-6598. When possible provide 3 hr PN for all rqr briefings.

AIRSPACE: CLASS D.
RADIO AIDS TO NAVIGATION: NOTAM FILE TCM.
 (T) **TACAN** Chan 33 TCM (109.6) N47°08.86' W122°28.50' at fld. 283/15E.
 No NOTAM MP 0800-2300Z± Wed
ILS 109.9 I-MAR Rwy 16. Class 1A. Rwy 16-34 backcourse unusable. Rwy 16-34 No NOTAM MP 0800-2300Z± Tue and Thu.
ILS 108.5 I-TCM Rwy 34. Class IIE. Rwy 16-34 backcourse unusable. Rwy 16-34 No NOTAM MP 0800-2300Z± Tue and Thu.

MEAD FLYING SERVICE (7ØS) 1 N UTC-8(-7DT) N47°47.23' W117°21.49' SEATTLE
 1905 TPA—2505(600) NOTAM FILE SEA
RWY 16-34: H2481X30 (ASPH)
RWY 16: Trees.
RWY 34: Trees.
AIRPORT REMARKS: Unattended. No winter maintenance. Rwy 16 rwy markings faded. Rwy 34 rwy markings faded.
AIRPORT MANAGER: 253-880-7805
COMMUNICATIONS: CTAF 122.9
CLEARANCE DELIVERY PHONE: For CD ctc Spokane Apch at 509-742-2522

MEARS FLD (See CONCRETE on page 229)