

**MIDWAY ATOLL****HENDERSON FLD** (MDY)(PMDY) 0 SW UTC-11 N28°12.09' W177°22.88'

HAWAIIAN ISLANDS

12 B Class IV, ARFF Index A NOTAM FILE MDY

P-1B

**RWY 06-24:** H7800X150 (ASPH) S-120, D-230, 2D-430 PCN 56 F/A/W/U MIRL

IAP

**RWY 06:** REIL. PAPI(P4L)—GA 3.0° TCH 80'.**RWY 24:** REIL. PAPI(P4L)—GA 3.0° TCH 80'.**RUNWAY DECLARED DISTANCE INFORMATION****RWY 06:** TORA-7800 TODA-7800 ASDA-7800 LDA-7800**RWY 24:** TORA-7800 TODA-7800 ASDA-7400 LDA-7400**SERVICE:** LGT ACTVT REIL Rwy 06 and 24; PAPI Rwy 06 and 24; MIRL Rwy 06-24-126.2.

**AIRPORT REMARKS:** Attended 1900-0400Z. Use freq 126.2 for all inbound and outbound communications. Be alert for heavy bird strike hazards at all times. Current bird activity status avbl during initial ctc inbound and prior to tkf and ldg on freq 126.2. Arpt clsd to all tran acft. Arpt open for ETOPS and approved acft ops only. Approved acft opns permitted only during hrs of darkness Nov-Jun due to heavy bird activity. PPR for ldg for approved acft opns from arpt manager 24 hrs in advance due to heavy bird activity call 808-954-4829. Except when necessary for tkf and ldg, all acft maintain minimum alt of 5,000 MSL within 12 miles of arpt. Arpt pri ctc (808) 674-1237. Backup contact sat phone Arpt Manager 011-8816-327-20578, USFWS Refuge Manager 011-8816-327-33725, DBSI Manager 001-8816-327-33825. Landing fee.

**AIRPORT MANAGER:** 808-954-4829**WEATHER DATA SOURCES:** AWOS-3P 118.325 (808) 674-9286.**COMMUNICATIONS:** CTAF 122.9**AIRSPACE:** CLASS E.**RADIO AIDS TO NAVIGATION:** NOTAM FILE MDY.**MIDWAY NDB (HW)** 400 MDY N28°12.25' W177°22.75' at fld. 16/10E.**COMM/NAV/WEATHER REMARKS:** No ATCT ops. Inbound acft ctc 100 NM out for advisories. CTAF not monitored ctc freq 126.2. Freq 126.2 monitored 1900-0400Z and during approved acft ops.