

NAPLES MUNI (APF)(KAPF) 2 NE UTC-5(-4DT) N26°09.15' W81°46.54'

8 B Class I, ARFF Index A NOTAM FILE APF

MIAMI
H-8H, L-21D, 23B
IAP, AD

RWY 05-23: H6600X150 (ASPH-GRVD) D-75 PCR 210 F/B/X/T

MIRL

RWY 05: REIL. PAPI(P4R)—GA 3.5° TCH 31'. Thld dsplcd 800'. Road. Rgt tfc.

RWY 23: REIL. PAPI(P4L)—GA 3.5° TCH 49'. Thld dsplcd 799'. Fence.

RWY 14-32: H5001X100 (ASPH-GRVD) S-75, D-75 PCR 320 F/B/X/T MIRL

RWY 14: REIL. PAPI(P4L)—GA 3.5° TCH 41'. Thld dsplcd 128'. Trees. Rgt tfc.

RWY 32: REIL. PAPI(P4L)—GA 3.5° TCH 48'. Thld dsplcd 451'. Trees.

RWY NE-SW: 1850X100 (TURF)

RUNWAY DECLARED DISTANCE INFORMATION

RWY 05: TORA-5800 TODA-5800 ASDA-5800 LDA-5000

RWY 14: TORA-5001 TODA-5001 ASDA-4550 LDA-4422

RWY 23: TORA-5800 TODA-5800 ASDA-5800 LDA-5000

RWY 32: TORA-5001 TODA-5001 ASDA-4873 LDA-4422

SERVICE: S4 FUEL 100LL, JET A, A+, UL94 OX 3, 4 LGT When ATCT clsd ACTVT REIL Rwy 05, 14, 23 and 32; PAPI Rwy 14 and 32; MIRL Rwy 05-23 and 14-32—CTAF.

NOISE: Extny noise sensitive area; use noise abatement procs. Voluntary restrictions exist for all acft ops 0300-1200Z†.

AIRPORT REMARKS: Attended 1100-0300Z†. Full svc fuel not avbl dly 0130-1030Z†. Clsd to acft exceeding 75,000 lbs max GWT dual gear indcd on acft orgp cert issued by manufacturer. Runups NA 0300-1200Z†; Twy A runup pads for Rwy 05-23 piston acft only; jet acft runup area Twy C btw Twy C3 and Twy D PPR—ATCT. Twy C frm C1 to ER Rwy 32 not visible frm ATCT. Rwy NE-SW mkd with pavers and PVC pipes. Rwy 23 dsngnd calm wind rwy for arrs 0300-1100Z†. Rwy 5 dsngnd calm wind rwy for deps 0300-1100Z†. APF GA aprn ctn obst lgt poles. PPR US customs svc Mon-Sun 1530-0000Z† PPR—239-430-9321. Wx mod acft notify ops 24 hrs prior to arr 239-564-1692. US Customs and Border Protection User Fee Arprt.

AIRPORT MANAGER: 239-643-0733

WEATHER DATA SOURCES: ASOS 134.225 (239) 643-9886.

COMMUNICATIONS: CTAF 128.5 ATIS 134.225 (239) 643-5230

RCO 122.5 (MIAMI RADIO)

® FORT MYERS APP/DEP CON 119.75 West 124.125 East (1100-0500Z†)

® MIAMI CENTER APP/DEP CON 134.75 (0500-1100Z†)

TOWER 128.5 (1100-0300Z†) GND CON 121.6 CLNC DEL 118.0

CLNC DEL 124.125 (When twr clsd, monitored by Fort Myers App Con)

CLEARANCE DELIVERY PHONE: For CD if una to ctc on FSS freq, ctc Ft Myers Apch at 239-416-1026, when Apch clsd ctc Miami ARTCC at 305-716-1731.

AIRSPACE: CLASS D svc 1100-0300Z†; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE RSW.

LEE COUNTY (VL) (H) VORTAC 114.15 RSW Chan 88(Y) N26°31.79' W81°46.55' 182° 22.6 NM to fld. 25/2W.

VOR unusable:

025°-040° byd 40 NM

075°-095° byd 40 NM

110°-116° byd 40 NM

117°-127° byd 40 NM blo 2,300'

117°-127° byd 57 NM

CYPRESS (L) DME 108.6 CYY Chan 23 N26°09.21' W81°46.69' at fld. 9. NOTAM FILE APF.

DME unusable:

215°-315°

COMM/NAV/WEATHER REMARKS: UNICOM freq: For FBO svc ctc—128.825.

