

## CONTINUED FROM PRECEDING PAGE

## RUNWAY DECLARED DISTANCE INFORMATION

RWY 10L:TORA-10001 TODA-10001 ASDA-9351 LDA-8151

RWY 10R:TORA-3214 TODA-3214 ASDA-3214 LDA-3214

RWY 14:TORA-6926 TODA-6926 ASDA-6000 LDA-6000

RWY 28L:TORA-3214 TODA-3214 ASDA-3214 LDA-3214

RWY 28R:TORA-10001 TODA-10001 ASDA-9051 LDA-8240

RWY 32:TORA-6926 TODA-6926 ASDA-6926 LDA-6513

## ARRESTING GEAR/SYSTEM

RWY 14: EMAS

SERVICE: S4 FUEL 100LL, JET A OX 1, 2, 3, 4

NOISE: Noise abatement procedures in effect. Multiengine flight training prohibited SS to SR, Sun and hol, strict environmental operating Stage 2 acft 0300-1200Z± call noise abatement officer 561-471-7467.

AIRPORT REMARKS: Attended continuously. Migratory birds on and in/ov arpt. SAID in use. Operate transponders with altitude reporting mode and ADS-B (if equiped) enabled on all airport surfaces. Class I ARFF Index C. Index D ARFF equipment avbl, 24 hr PPR. Rwy 14-32 safety area not std sfc varns. Rwy 10L-28R safety area not std sfc varns. Be alert, Twy L is lctd btn Rwys 10L-28R and 10R-28L. Twy L is wider and longer than Rwy 10R-28L, do not confuse Twy L for rwy. Acft with wingspan of 118' or greater is prohibited on Twy L. Acft with wingspans grtr than 118' may not opr on Twy E, Twy W, Twy Y and Twy F NW of Twy A. 24 hr advn notice or imt reporting upon ldg for acft equipped with weather modification or geoengineering equip ctc arpt ops 561-471-7420. 24 hr PPR for acft with wingspans greater than 171'. Acft with wingspans grtr than 49' may not oper simul on Rwy 10R-28L and Twy R. Rwy 14 LAHSO signage not std. Twy L3 east surface painted holding position sign not std. Be alert, Rwy 28L and Rwy 28R thlds staggered by 5400'. Flight Notification Service (ADCUS) avbl. NOTE: See Special Notices—Arrival Alert.

AIRPORT MANAGER: 561-471-7420

WEATHER DATA SOURCES: ASOS 123.75 (561) 444-7590. LLWAS. TDWR.

COMMUNICATIONS: D-ATIS 123.75 UNICOM 122.95

RCO 122.4 (MIAMI RADIO)

RCO 122.1R 115.7T (MIAMI RADIO)

Ⓡ APP/DEP CON 128.3 125.2 (South)

TOWER 118.75 119.1 GND CON 121.9 CLNC DEL 121.6

CPDLC

PDC

AIRSPACE: CLASS C svc ctc APP CON.

RADIO AIDS TO NAVIGATION: NOTAM FILE PBI.

(VH) (H) VORTAC 115.7 PBI Chan 104 N26°40.80' W80°05.19' at fld. 16/3W.

VOR unusable:

005°-015° byd 40 NM blo 5,000'

005°-015° byd 63 NM

016°-044° byd 40 NM

052°-062° byd 100 NM

052°-062° byd 40 NM blo 6,000'

052°-062° byd 81 NM blo 8,000'

185°-195° byd 13 NM

209°-219° byd 40 NM

257°-267° byd 40 NM

305°-324° byd 40 NM

332°-348° byd 40 NM

349°-353° byd 40 NM

354°-004° byd 40 NM blo 3,000'

354°-004° byd 53 NM

TACAN AZIMUTH unusable:

286°-296° byd 28 NM

ILS/DME 111.9 I-PBI Chan 56 Rwy 10L. Class IT.

ILS 111.9 I-PWB Rwy 28R. Class IT.

COMM/NAV/WEATHER REMARKS: 24-hr PPR rq for all acft equipped with wx modification eqpt or acft cpbl of wx modification

and/or geoengineering by ctc The Dept of Aprt Communications Cntr at (561) 471-7420.

WHITEHOUSE NOLF (NEN)(KNEN) TC N30°20.97' W81°52.02'

AIRSPACE: CLASS D svc ATCT manned during scheduled operations only; other times CLASS G.

JACKSONVILLE

H-8H, 12F, L-21D, 24G, AD