

ST PAUL DOWNTOWN HOLMAN FLD (STP)(KSTP) P (ARNG) 1 S UTC-6(-5DT) N44°56.08'

TWIN CITIES

W93°03.62'

H-21, L-121, 141, A

705 B TPA—1905(1200) LRA NOTAM FILE STP

IAP, AD

RWY 14-32: H6491X150 (ASPH-GRVD) S-83, D-111, 2D-197

HIRL

RWY 14: MALSR. PAPI(P4R)—GA 3.0° TCH 50'. RVR-TR Thld dspcd 343'. Road.**RWY 32:** REIL. PAPI(P4L)—GA 3.0° TCH 40'. RVR-TR Thld dspcd 382'. Trees.**RWY 13-31:** H4004X150 (ASPH-GRVD) S-97, D-135, 2S-175,


2D-228 HIRL

RWY 13: PAPI(P4L)—GA 3.0° TCH 40'.**RWY 31:** REIL. PAPI(P4L)—GA 3.0° TCH 45'. Brush.**RWY 09-27:** H3642X100 (ASPH) S-12.5, 2S-175 MIRL**RWY 09:** Tree.**RWY 27:** PAPI(P4R)—GA 4.0° TCH 40'. Tree. Rgt tfc.**RUNWAY DECLARED DISTANCE INFORMATION****RWY 09:** TORA-3642 TODA-3642 ASDA-3642 LDA-3642**RWY 13:** TORA-4004 TODA-4004 ASDA-4004 LDA-4004**RWY 14:** TORA-6491 TODA-6491 ASDA-6491 LDA-6148**RWY 27:** TORA-3642 TODA-3642 ASDA-3642 LDA-3642**RWY 31:** TORA-4004 TODA-4004 ASDA-4004 LDA-4004**RWY 32:** TORA-6491 TODA-6491 ASDA-6491 LDA-6109**ARRESTING GEAR/SYSTEM****RWY 14:** EMAS**RWY 32:** EMAS

SERVICE: S4 **FUEL** 100LL, JET A **OX** 1, 2 **LGT** When twr clsd, to increase ints and **ACTIVATE** MALSR Rwy 14, REIL Rwy 31, PAPI Rwy 13, Rwy 27, and Rwy 31, HIRL Rwy 14-32 and Rwy 13-31, MIRL Rwy 09-27—CTAF. PAPI Rwy 14 and Rwy 32 operate continuously. Rwy 13 PAPI unusable byd 4° right of cntrln and inside 0.5 NM. Rwy 14 PAPI unusable byd 8° left of cntrln. Arpt beacon on west edge of arpt. **MILITARY—A-GEAR** Rwy 14 EMAS 280' x 162'. Rwy 32 EMAS 225' x 162'. **FUEL** JET A Idg fee, ctc FBO. J8(Mil), A (1100-0500Z† Mon-Fri; 1300-0400Z† Sat-Sun; C651-227-8108, OT PN 4 hr.) (NC-100LL)

NOISE: Voluntary noise abatement procs in efct. See arpt website for more info.

AIRPORT REMARKS: Attended continuously. Deer, birds and wildlife on and invof arpt. Arpt CLOSED to acft over 100,000 lbs. Complex airport geometry. Verify correct compass heading prior to departure. Cold temperature airport. Altitude correction required at or below -30C. PPR acft over 100,000 lbs, ctc arpt manager. Rwy 14 is calm wind rwy when twr clsd. When using Rwy 27 or Rwy 31, hazardous river tfc may exist. Southeast arrivals and departures avoid tfc pattern ops at South St. Paul arpt 164° 5 NM at and blo 1720' MSL. Twy A clsd between Twy A3 and Twy A4 except for wingspan less than 101'. Expect helicopter ops on Twy A in the vicinity of the ctrl twr, north to the approach end of Rwy 14. Twy B clsd between MN jet ramp and Twy A (southern corner) except for wingspan less than 72' due to flood wall obstacle. Flight Notification Service (ADCUS) avbl. Ldg fee.

AIRPORT MANAGER: 651-224-4306**WEATHER DATA SOURCES:** ASOS 118.35 (651) 312-8888. LAWRS.**COMMUNICATIONS:** CTAF 119.1 ATIS 118.35 UNICOM 122.95® **MINNEAPOLIS APP/DEP CON** 121.2**MINNEAPOLIS APCH CLNC DEL** 121.675 (when twr clsd)**ST PAUL TOWER** 119.1 (1200-0400Z† Mon-Fri, 1300-0400Z† Sat-Sun)**GND CON** 121.675 **CLNC DEL** 121.675**ARNG OPS** 126.2 347.7**CLEARANCE DELIVERY PHONE:** When ATCT clsd, for CD ctc Minneapolis Apch on 121.675.**AIRSPACE:** CLASS D svc 1200-0400Z† Mon-Fri, 1300-0400Z† Sat-Sun; other times CLASS E.**CONTINUED ON NEXT PAGE**

CONTINUED FROM PRECEDING PAGE

VOR TEST FACILITY (VOT) 114.4

RADIO AIDS TO NAVIGATION: NOTAM FILE PNM.

GOPHER (VH) (H) VORTACW 117.3 GEP Chan 120 N45°08.74' W93°22.39' 127° 18.4 NM to fld. 877/6E.

VOR unusable:

025°-080° blo 5,000'
061°-071° byd 40 NM
067°-080° byd 47 NM blo 3,000'
239°-277° byd 40 NM blo 18,000'
240°-260° byd 5 NM
275°-285° byd 10 NM blo 4,000'
330°-345° byd 13 NM blo 3,000'

TACAN AZIMUTH unusable:

025°-080° blo 5,000'
145°-155° byd 37 NM blo 3,800'
230°-250° byd 38 NM blo 3,400'
275°-285° byd 10 NM blo 4,000'
330°-345° byd 13 NM blo 3,000'

DME unusable:

145°-155° byd 37 NM blo 3,800'
275°-285° byd 10 NM blo 4,000'
330°-345° byd 13 NM blo 3,000'

ILS/DME 111.5 I-VKG Chan 52 Rwy 14. Class IB. Unmonitored when twr clsd. LOC unusable 9° right of course. Glideslope unusable 4° left or right of course. LOC unusable byd 6° left of course.

ILS/DME 111.5 I-BAO Chan 52 Rwy 32. Class IA. DME unusable blo 3,500' byd 25° left of course. Unmonitored when twr clsd.

COMM/NAV/WEATHER REMARKS: Emerg frequency 121.5 not avbl at twr.

SAUK CENTRE MUNI (D39) 2 SE UTC-6(-5DT) N45°42.40' W94°55.99'

1242 B TPA-2042(800) NOTAM FILE PNM

RWY 14-32: H3296X75 (ASPH) MIRL

RWY 14: REIL. PAPI(P4L)—GA 3.0° TCH 23'.

RWY 32: REIL. PAPI(P4L)—GA 3.0° TCH 22'.

RWY 08-26: 2404X120 (TURF)

RWY 08: Brush.

RWY 26: Road.

SERVICE: S3 **FUEL** 100LL **LGT** Rwy 14-32 MIRL preset to low; to incr insty and ACTVT REIL Rwy 14 & Rwy 32; PAPI Rwy 14 & Rwy 32—CTAF.

AIRPORT REMARKS: Attended Mon-Fri 1400-2300Z†. Fuel avbl 24 hrs with credit card. Rwy 08-26 not plowed winter months. Rwy 08-26 marked with yellow cones.

AIRPORT MANAGER: 320-352-2203

WEATHER DATA SOURCES: AWOS-3 118.475 (320) 352-0136.

COMMUNICATIONS: CTAF 122.9

® **MINNEAPOLIS CENTER APP/DEP CON** 126.1

CLEARANCE DELIVERY PHONE: For CD ctc Minneapolis ARTCC at 651-463-5588.

RADIO AIDS TO NAVIGATION: NOTAM FILE AXN.

ALEXANDRIA (VL) (DH) VORW/DME 115.95 AXN Chan 106(Y)

N45°57.50' W95°13.96' 133° 19.6 NM to fld. 1367/7E.

VOR unusable:

045°-060° byd 30 NM blo 6,400'

DME unusable:


045°-060° byd 30 NM blo 6,400'

146°-153° byd 15 NM

TWIN CITIES

L-14H

IAP



SCOTTS SPB (See CRANE LAKE on page 160)

SCOTT N48°15.59' W92°28.48' NOTAM FILE CDD.

GREEN BAY

NDB (MHW) 385 SCG at Scotts. 1155/1W. (VFR only).

SKY HARBOR SPB (See EVELETH on page 165)

SKY HARBOR (See DULUTH on page 163)