

NASHVILLE

JOHN C TUNE (JWN)(KJWN) 1 NW UTC-6(-5T) N36°10.98' W86°53.19'

ST LOUIS

501 B NOTAM FILE BNA

H-6K, 9A, L-16I

RWY 02-20: H6001X100 (ASPH-GRVD) S-35, D-97 MIRL 0.7% up N

IAP, AD

RWY 02: REIL. PAPI(P4L)—GA 3.0° TCH 40'. Tree.

RWY 20: REIL. PAPI(P4L)—GA 3.0° TCH 40'. Tree. Rgt tfc.

RUNWAY DECLARED DISTANCE INFORMATION

RWY 02: TORA-6001 TODA-6001 ASDA-6001 LDA-6001

RWY 20: TORA-6001 TODA-6001 ASDA-6001 LDA-6001

ARRESTING GEAR/SYSTEM

RWY 20: EMAS

SERVICE: S4 FUEL 100LL, JET A+ 0X2, 3 LGT When ATCT clsd ACTVT REIL Rwy 02 & 20; PAPI Rwy 02 and 20; MIRL Rwy 02-20—CTAF.

AIRPORT REMARKS: Attended continuously. Birds & deer invof arpt. Engineered Material Arresting System (EMAS) 186' long by 121' wide lctd 560' fm dep end Rwy 20. Twy R1 clsd to acft wingspan more than 49'. Twy R2 clsd to acft wingspan more 79'.

AIRPORT MANAGER: 615-275-1783

WEATHER DATA SOURCES: AWOS-3 (615) 350-6222 LAWRS.

COMMUNICATIONS: CTAF 119.45 ATIS 127.075 615-350-6222

® NASHVILLE APP/DEP CON 119.35

JOHN TUNE TOWER 119.45 (1300-0300Z±) GND CON 121.7 CLNC DEL 121.7 124.55

CLEARANCE DELIVERY PHONE: When ATCT clsd for CD ctc Nashville Apch on 124.55, if unable call 615-695-4524.

AIRSPACE: CLASS D svc 1200-0200Z±; other times CLASS G.

RADIO AIDS TO NAVIGATION: NOTAM FILE BNA.

NASHVILLE (VH) (H) VORTACW 114.1 BNA Chan 88 N36°08.22' W86°41.09' 288° 10.2 NM to fld. 566/2W.

TACAN AZIMUTH unusable:

062°-069° blo 6,000'

DME unusable:

062°-069° blo 6,000'

VOR unusable:

062°-069° blo 6,000'

063°-070° byd 40 NM

163°-165° byd 40 NM

181°-191° byd 40 NM blo 18,000'

192°-239° byd 40 NM

ILS/DME 110.3 I-JWN Chan 40 Rwy 20. Class IA.

COMM/NAV/WEATHER REMARKS: Ctc FBO 122.85. Bleedover ocr all freqs 1.75 NM north of rwy.